

IKA® Heating Heating baths



1

HB 4 basic

Heating bath with 4 l useful volume,
page 69.

2

HBR 4 digital

Heating bath with 4 l useful volume,
digital display and magnetic stirring
drive, page 69

3

H 240

Ring set to cover the heating baths,
page 71.

IKA® Heating Heating baths

HB 4 basic Heating bath

The heating bath is characterized by the following features:

- Cylindrical bath shape
- High-grade recyclable materials
- The heating elements are situated underneath the bath vessel
- Either low viscosity oil or water can be used as the heat transfer fluid
- Useful volume of 4 liters
- Heat output 1,000 W
- Infinitely adjustable safety temperature limiter acc. to DIN 12877
- The safety elements are checked when the unit is switched on
- Double jacket and carrying handles provide protection against burns

Heat output	1,000 W
Temperature range	RT - 225 °C
Setting tolerance	± 5 K
Deviation	± 5 K
Temperature display	Scale
Safety class acc. to DIN 12877	2
Stirring function	no
Useful volume	4 l
Material	stainl. steel (1.4301)
Outer diameter	340 mm
Inner diameter	200 mm
Outer height	250 mm
Inner height	160 mm
Weight	3.9 kg
Permissible humidity	80 %
Permissible ambient temperature	5 - 40 °C
Protection class acc. to DIN EN 60529	IP 42

Accessories (Page):

H 240 Ring set (71),

Ident. No.	Ident. No.
2520000	2520001
230 V 50/60 Hz	115 V 50/60 Hz

HBR 4 digital Heating bath

The digital heating bath is characterized by the following features:

- Digital display presents rated, actual and safety temperature as well as speed
- Fuzzy logic control
- Integrated magnetic stirring drive to circulate the tempering fluid, which contributes to improved heat distribution
- See HB 4 basic for additional features

Heat output	1,000 W
Temperature range	RT - 200 °C
Setting tolerance	± 1 K
Deviation (3 l H ₂ O)	± 0.4 K
Temperature display	digital
Safety class acc. to DIN 12877	2
Stirring function	yes
Speed range	50 - 800 rpm
Useful volume	4 l
Material	stainl. steel (1.4301)
Outer diameter	340 mm
Inner diameter	200 mm
Outer height	250 mm
Inner height	160 mm
Weight	4.4 kg
Permissible ambient temperature	5 - 40 °C
Permissible humidity	80 %
Protection class acc. to DIN EN 60529	IP 21

Accessories (Page):

H 240 Ring set (71),
H 159 Intermediate bottom (71),
IKAFLON® Stirring bars (19)

Ident. No.	Ident. No.
2602300	2602301
230 V 50/60 Hz	115 V 50/60 Hz