

Data Sheet

Mixing / Magnetic Stirrers



Mini MR standard IKAMAG®

Magnetic stirrer without heating, for stirring quantities up to 800 ml (H₂O).

- Infinitely variable speed from 0 - 1,500 rpm
- White set-up plate suitable for observing color reactions

Accessories: IKAFLON® 10 Magnetic stirring bar, IKAFLON® 15 Magnetic stirring bar, IKAFLON® 20 Magnetic stirring bar, IKAFLON® 25 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar, TRIKA® 25 Magnetic stirring bar, RSE Stirring bar remover

Technical Data	
Number of stirring positions	1
Stirring quantity max. per stirring position (H ₂ O) [l]	0.8
Motor rating input [W]	4
Motor rating output [W]	0.5
Speed range [1/min]	0 - 1500
Speed control	stepless
Set-up plate material	polyester
Set-up plate dimensions [mm]	115 x 115
Dimensions (W x H x D) [mm]	115 x 40 x 130
Weight [kg]	0.23
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 42
Voltage [V]	100 - 240
Frequency [Hz]	50/60
Power input [W]	4
Ident. No.	2677000