

Wolf's Oven Range



Features:

- Temperature range:
40C to 250C
40C to 300C for 50L and above
- Aluminium-coated mild steel or stainless steel interior
- Direct reading hydraulic controls
- Safety thermostat with indicator

Optional Extras

- Fan assisted circulation (30 to 350L only)
- Digital control and readout
- Programmable controllers
- Solid door
- Toughened glass door
- Toughened glass door with solid outer door
- Various timers (50-350L only)

Design

The exterior is constructed from sheet steel finished in easy clean stove powder paint.

The interior is fitted with fixed shelf runners with removable chrome plated steel wire grid shelves.

The door and chamber are fitted with silicone seals for excellent insulation against heat and is easy to clean.

The ovens are heated by incoly sheathed elements and are powered by 220/240V single phase supply.



SPECIFICATIONS

GP series	10	20	30	40	50
Ext Dims (mm) HxWxD	415x375x350	540x375x382	570x415x422	670x415x422	615x590x422
Int. Dims (mm) HxWxD	150x275x243	275x275x275	305x315x315	405x315x315	325x490x315
Capacity (Litres)	10	20	30	40	50
Shelf Positions	1	2	3	3	3
Number of Shelves	1	2	2	2	2
Max. Load Height	105	190	320	320	240
Shelf Size (mm) WxD	240x208	240x240	280x280	280x280	455x270
Power Rating (Watts)	350	500	750	1000	1000
Net Weight	10	15	25	25	30
Fluctuation (Hydraulic) at 38C	+/-0.75C	+/-0.75C	+/-0.75C	+/-0.75C	+/-0.75C
Fluctuation (digital) at 38C	+/-0.5C	+/-0.5C	+/-0.5C	+/-0.5C	+/-0.5C

GP series	75	100	120	150	180
Ext Dims (mm) HxWxD	623x590x567	735x590x422	735x590x659	845x590x659	957x590x659
Int. Dims (mm) HxWxD	333x490x460	445x490x460	445x490x552	555x490x552	667x490x552
Capacity (Litres)	75	100	120	150	180
Shelf Positions	3	4	4	5	6
Number of Shelves	2	3	3	3	4
Max. Load Height	248	360	360	470	582
Shelf Size (mm) WxD	455x415	455x415	445x507	455x507	455x507
Power Rating (Watts)	1250	1250	1500	1500	1750
Net Weight	35	40	45	50	55
Fluctuation (Hydraulic) at 38C	+/-0.75C	+/-0.75C	+/-0.75C	+/-0.75C	+/-0.75C
Fluctuation (digital) at 38C	+/-0.5C	+/-0.5C	+/-0.5C	+/-0.5C	+/-0.5C

GP series	210	240	280	350
Ext Dims (mm) HxWxD	957x590x749	1178x590x659	941x750x769	1104x750x769
Int. Dims (mm) HxWxD	642x490x642	888x490x552	651x650x662	814x650x662
Capacity (Litres)	210	240	280	350
Shelf Positions	6	8	6	7
Number of Shelves	4	4	4	4
Max. Load Height	582	803	566	729
Shelf Size (mm) WxD	455x597	455x507	615x617	615x617
Power Rating (Watts)	2000	2250	2250	2500
Net Weight	65	73	78	95
Fluctuation (Hydraulic) at 38C	+/-0.75C	+/-0.75C	+/-0.75C	+/-0.75C
Fluctuation (digital) at 38C	+/-0.5C	+/-0.5C	+/-0.5C	+/-0.5C