

GALAXY...THE RIGHT CO₂ INCUBATOR FOR YOUR LAB

Galaxy incubators are offered in a range of three sizes and two models, with an unrivaled number of options.

All Galaxy incubators feature:

SIX-SIDED, DIRECT HEATING PROFILE:

Pioneered in Galaxy incubators, the unique direct-heat profile gently bathes the cells in a consistent atmosphere through gentle convection. This system guards against wide fluctuations in temperature and CO₂ that can shock cells, as seen in traditional forced-air culture systems.

FANLESS DESIGN:

Galaxy incubators pioneered elimination of conventional fans, replacing them with our unique heating profile, which sets up a gentle circulation of air. By removing the fan, Galaxy incubators have eliminated a classic source of repeated contamination, allowing the entire incubator — including upper shelf — to be utilized while maintaining uniformity. In addition, since there is no fan, there is no need for an expensive internal HEPA filter that needs to be replaced frequently.

IR CO₂ SENSOR:

Standard in all Galaxy models, is our unique InfraRed (IR) CO₂ sensor. This sensor offers specific measurement and accurate control of CO₂ levels. The traditional thermal conductivity (TC) sensor is highly sensitive to changes in chamber humidity and temperature fluctuations, and is therefore fundamentally unsuitable for use in CO₂ incubators. Uniquely, the Galaxy IR Sensor can remain in the chamber during the entire high-temperature disinfection cycle, ensuring that all chamber components are sterilized.

SIMPLIFIED CLEANING:

On all models, the chambers are pressed from a single sheet of stainless steel, with no welds or seams, eliminating another potential source of contamination. In combination with the easily-removable, replaceable shelves, this makes chamber cleaning a rapid and efficient process, so more time can be spent engaged in science and less with maintaining the instrument.

Available in 14L, 48L & 170L capacities, and in choice of sophisticated "R" models with advanced controller, or economical "S" models with LED display. Back row: Galaxy 170 S (left) & 170 R. Front row: Galaxy 14 S (left) and 48 R. Galaxy 48 S not shown.

UNIQUE RANGE OF MODEL SIZES:

In common with our 170L incubators, our 48L and 14L incubators incorporate all of the superior design and innovation of the larger units, in a smaller format. These units offer the ideal environment for hypoxic applications, research requiring isolation, and IVF research.

OPTIONS: (see page 10 for added details)

Galaxy CO₂ incubators come with a wide variety of options allowing customization to meet your exact requirements and level of sophistication. With High-Temperature Disinfection (HTD), three levels of O₂ control, and new active disinfection and humidification options, there is a Galaxy incubator for every application.

NEW FEATURES:

- **25mm Access Port Standard**

Available for adding instrumentation or additional probes.

- **RS-232 Port Standard**

For communication and external instrument logging.

- **Perforated Shelves**

The unique design of the perforated shelving system optimizes temperature, CO₂ and especially RH recovery to minimize the effects of door openings and closings.

- **Innovative Sealed Inner Glass Door**

Available on 170L models, the new sealed inner glass door system allows viewing access to the samples while maintaining complete sample and environmental integrity. This system is designed to minimize costly CO₂ and N₂ consumption and to provide optimal sample stability and uniformity throughout the culturing process.



The **Galaxy 48 R & S Series** provide the luxury of owning a single-user, personal-sized 48L (1.7 cu. ft.) incubator. They offer the same standard features as the larger 170L models, including fanless design to allow for maximum capacity. Galaxy 48 models easily fit on a benchtop for

laboratories requiring small volume cell culture, and are ideal for isolation studies such as viral work.

Choose full-featured R Series or economical S Series models:


GALAXY 48 R

Galaxy 48 R incubators feature an integrated and heated outer-door window to allow viewing your cultures without compromising the culture environment.

They are ideally suited for hypoxic applications, including *in-vitro* fertilization (IVF) and stem cell research, with O₂ control option. The relatively compact 48L chamber substantially reduces the significant gas consumption often encountered when using larger incubators.

CONTROLLER:

The controller offers the same 72-hour data logging and diagnostic interface as on the 170 R described on page 4. Examples of graphical logging and alarm screens are shown below.



Temperature, humidity, CO₂ control, door openings and alarms are captured in a 72-hour downloadable record, and shown on the large display for easy monitoring.



Chamber alarm screen enables password protected alarm setting and easy access to any alarm information.

FEATURES:

- **Convenient benchtop size and footprint** — only 48 x 47 cm [18.9" x 18.5"].
- **Integrated, heated, viewing window in outer door** allows observation without disturbing cultures.
- **Seamless, fanless design.**
- **RS-232 and 25mm access port.**
- **Stackable.**
- **Low gas consumption.**
- **Perforated shelving** to facilitate faster recoveries.
- **Large volume humidity pan.**
- **CO₂ HEPA filtration.**

OPTIONS (see page 10 for details):

- **High-temperature disinfection.**
- **O₂ control** (Choose 1-19%, 0.1-19%, 1-95%).
- **Two split inner glass doors.**
- **Humidity alert package** (display and alarm).
- **BMS management system relays.**



Galaxy 48 R features an advanced controller and extra large display screen. (Shown with viewing window open.)

GALAXY 48 S

Galaxy 48 S Series incubators are entry-level models, offering the same superior performance as 48 R models. The S Series use an easily-read LED interface and includes an integrated viewing window, standard 25mm access port and RS-232 communications package. They are ideal for laboratories with limited space to house large incubators, or for standard cell culture applications where the larger 170 liter capacity systems are not required.

FEATURES:

- Small footprint with mid-sized capacity.
- Seamless chamber.
- Fanless design.
- 25mm access port.
- RS-232 port.
- User-friendly LED display.

OPTIONS (see page 10 for details):


- BMS management system relays.
- Two split inner glass doors.



Galaxy 48 S incubators come with an easy-to-use keypad and viewing window.



All Galaxy incubators feature a seamless chamber, with no corners, seams or welds, to minimize contamination risk.



The small size of Galaxy 48 and 14 incubators make them ideally suited to critical applications such as in-vitro fertilization, where sample isolation is imperative.

CUSTOMIZE YOUR INCUBATOR WITH THESE OPTIONS

HIGH TEMPERATURE DISINFECTION:

Available on the 170 R & S, and 48 R models.

- 120°C 4-hour cycle.
- One-touch operation.
- CO₂ Sensor remains in the chamber.
- Ensures a clean and disinfected environment for cell culture.

O₂ CONTROL:

Available on the 170 R, 48 R, and 14 S.



- Up to three levels of control options.
- 1 - 19% for most common hypoxic applications.
- 0.1 - 19% for more stringent oxygen requirements.
- 1 - 95% for hyperoxic and hypoxic incubation.
- Ideal for Stem Cell, Oncology, and IVF studies.

NEW ACTIVE HUMIDIFICATION SYSTEM (AHS):

Available on the 170 R.



- Rapid humidification of the CO₂ chamber.
- User-defined humidification settings to 95%.
- Non-condensing humidity.
- Ideal for low sample volume and microtiter plate applications.
- External UV disinfection of humidified atmosphere.

NEW COOLING SYSTEM:

Available on the 170 R.



- Allows studies at or below ambient temperature.
- Effectively cools to 10°C below ambient temperature.
- Redesign offers an efficient and uniformly cooled chamber.

UV DISINFECTION SYSTEM:

Available on the 170 R.



- Active and continuous UV disinfection of internal atmosphere.
- Gently passing air over an external UV module.
- No risk to cells of UV exposure.

BUILDING MANAGEMENT SYSTEM (BMS) RELAY:

Available on all models.

- Relay for integration with building alarm system.

COPPER CHAMBER:

Available on 170 R and S.

- Oxidizing copper chamber provides an added contamination protection.

SPLIT INNER DOORS:

Available on 170 R & S, and 48 R & S.



- 4 or 8 Split inner glass door options available on 170 R & S models.
- 2-Split inner glass door option available on 48 R & S models.
- Offers enhanced chamber temperature uniformity and reduced gas consumption.
- Maintains easy access to samples.

BIOCOMMAND® SFI:

Available on all models.

- Data logging and control software designed specifically for our CO₂ Incubators.
- Provides historical data logging and report generation to local computer, and for multiple units.
- Connects through RS-232 port.

Galaxy Incubator Model **	170 R	170 S	48 R	48 S	14 S
Standard, 120V	CO170R-120-0000	CO170S-120-0000	CO48R-120-0000	CO48S-120-0000	CO14S-120-0000
Standard, 230V	CO170R-230-0000	CO170S-230-0000	CO48R-230-0000	CO48S-230-0000	CO14S-230-0000
With High-Temp. Disinfection, 120V	CO170R-120-1000	CO170S-120-1000	CO48R-120-1000	—	—
With High-Temp. Disinfection, 230V	CO170R-230-1000	CO170S-230-1000	CO48R-230-1000	—	—
With 1 - 19% O ₂ Control, 120V	CO170R-120-0200	—	CO48R-120-0200	—	CO14S-120-0200
With 1 - 19% O ₂ Control, 230V	CO170R-230-0200	—	CO48R-230-0200	—	CO14S-230-0200
With High-Temp. & 1-19% O ₂ Control, 120V	CO170R-120-1200	—	CO48R-120-1200	—	—
With High-Temp. & 1-19% O ₂ Control, 230V	CO170R-230-1200	—	CO48R-230-1200	—	—

Additional Factory-Installed Options

O ₂ Control, 0.1 - 19%	P0628-5410	—	P0628-6280	—	—
O ₂ Control, 1 - 95%	P0628-5400	—	P0628-5260	—	—
Cooling System (below ambient) ∅	P0628-6810	—	—	—	—
Active Humidification ∅	P0628-6800	—	—	—	—
Active UV Disinfection System ∅	P0628-6790	—	—	—	—
Building Management System Relays	P0628-5540	P0628-5651	P0628-5340	P0628-5341	P0628-6300
Single Inner Glass Door	Standard	Standard	—	—	P0628-6210
Split Inner Doors - 2	—	—	P0628-5330	P0628-5330	—
Split Inner Doors - 4	P0628-6780	P0628-6780	—	—	—
Split Inner Doors - 8	P0628-6781	P0628-6781	—	—	—
Humidity Alert Package (Display and Alarm)	P0628-6820	—	P0628-6770	—	—
Internal Sealed Power Supply (IP66)	P0628-5560	P0628-5560	P0628-5350	P0628-5350	—
Copper Chamber	P0628-5430	P0628-5430	—	—	—

Accessories - Gas Management & Analysis

Two Stage CO ₂ Regulator	P0628-5010	P0628-5010	P0628-5010	P0628-5010	P0628-5010
Two Stage N ₂ Regulator	P0628-7220	—	P0628-7220	—	P0628-7220
CO ₂ Supply Line HEPA Filters (2)	P0628-5020	P0628-5020	P0628-5020	P0628-5020	P0628-5020
CO ₂ In-line Pressure Regulator	P0628-5030	P0628-5030	P0628-5030	P0628-5030	P0628-5030
CO ₂ Cylinder Auto-Changeover Controller	P0628-5000	P0628-5000	P0628-5000	P0628-5000	P0628-5000
Auto-Zero HEPA Filters (5)	P0628-5060	P0628-5060	P0628-5060	P0628-5060	P0628-5060
CO ₂ Gas Analyzer Kit	P0628-5040	P0628-5040	P0628-5040	P0628-5040	P0628-5040
Spare CO ₂ Gas Analyzer Tubes (10)	P0628-5050	P0628-5050	P0628-5050	P0628-5050	P0628-5050
Electronic CO ₂ Gas Analyzer	P0628-6150	P0628-6150	P0628-6150	P0628-6150	P0628-6150
Electronic CO ₂ & O ₂ Gas Analyzer	P0628-6831	P0628-6831	P0628-6831	P0628-6831	P0628-6831
Electronic CO ₂ & O ₂ Gas A. w/ °C & RH meas.	P0628-6832	P0628-6832	P0628-6832	P0628-6832	P0628-6832
Calibration Gas 5%, 20L Disposable Canister	P0628-7211	P0628-7211	P0628-7211	P0628-7211	P0628-7211
Control Valve & Flow Indicator for 20L Canister	P0628-6061	P0628-6061	P0628-6061	P0628-6061	P0628-6061
Calibration Gas 5%, 105L Disposable Canister	P0628-7210	P0628-7210	P0628-7210	P0628-7210	P0628-7210
0.3L/min Flow Regulator w/ pressure Gauge ††	P0628-7221	P0628-7221	P0628-7221	P0628-7221	P0628-7221

Accessories - Shelves, Pans & Stacking Stand

Multi-Position Shelf Rack	Standard	P0628-6390	P0628-5100	P0628-5100	P0628-6170
Additional Shelf, non-perforated	P0628-6241	P0628-6241	P0628-5070	P0628-5070	P0628-6180
Additional Shelf, perforated	P0628-6251	P0628-6251	P0628-5080	P0628-5080	P0628-7200
Additional Humidity Pan †	P0628-6260	P0628-6260	P0628-5940	P0628-5940	P0628-6200
Stacking Kit and Stand	P0628-6270	P0628-6270	P0628-6720	P0628-6720	P0628-6230 ∅∅
Stacking Kit - No Stand, with casters	P0628-6490	P0628-6490	P0628-5090	P0628-5090	—

Accessories - Electronics & Software

BioCommand® SFI Software	M1291-0054	M1291-0054	M1291-0054	M1291-0054	M1291-0054
--------------------------	------------	------------	------------	------------	------------

** Part numbers subject to change without notice. Additional incubator configurations are also available. Ordering them, or ordering custom options, will affect delivery and shipping. Not all options are compatible. Ask your NBS Sales Rep for quotation. All models are 50/60 Hz units.

† 2.5L humidity pan in 170L incubators, 0.5L pan in 48L units, and 0.3L pan in 14L systems. †† For Reusable 105L cylinder.

∅ Please check availability before ordering. Cooling option cannot be combined with High Temperature Disinfection options.

∅∅ Mounting bracket for stacking two units.

		Galaxy 170 R & S	Galaxy 48 R & S	Galaxy 14 S
Chamber	Volume	170 liters / 6.0 cu. ft.	48 liters / 1.7 cu. ft.	14 liters / 0.5 cu. ft.
Temperature Management	Range	4°C above ambient to 50°C	4°C above ambient to 50°C	5°C above ambient to 50°C
	Control	± 0.1°C	± 0.1°C	± 0.1°C
	Stability	± 0.1°C	± 0.1°C	± 0.1°C
	Uniformity	≤ ± 0.4°C	≤ ± 0.3°C	≤ ± 0.2°C
CO₂ Gas Management	Range	0.2 – 20%	0.2 – 20%	0.2 – 20%
	Control	± 0.1%	± 0.1%	± 0.1%
	Stability	± 0.2%	± 0.2%	± 0.2%
	Uniformity	± 0.1%	± 0.1%	± 0.1%
	Recovery (up to 90% setpoint)	0.7%/minute	0.7%/minute	> 0.7%/ minute
	Connections	6mm tubing	6mm tubing	6mm tubing
	Gas Service Pressure	0.35 bar / 5 psi	0.35 bar / 5 psi	0.35 bar / 5 psi
Humidity	Reservoir	Removable stainless pan	Removable stainless pan	Removable stainless pan
	Volume	2.5 liters	0.5 liters	0.3 liters
	Rh (@ 37°C)	up to 95%	Normal 90 - 95%	> 90% at 37°C
Shelves	Dimensions per Shelf \emptyset	51.9 x 42.6 cm (20.4" x 16.8")	35.1 x 26.1 cm (13.8" x 10.3")	22.0 x 18.4 cm (8.7" x 7.2")
	Shelves Provided	4	3	2
	Adjustability	R: 8 position. S: 4 position	6 position	4 position
Dimensions		W x D x H	W x D x H	W x D x H
	Chamber (mm)	540 x 451 x 693 mm	401 x 308 x 401 mm	233 x 208 x 294 mm
	Chamber (inches)	21.3" x 17.8" x 27.3"	15.8" x 12.1" x 15.8"	9.2" x 8.2" x 11.6"
	External (mm)	685 x 677 x 848 mm	484 x 475 x 648 mm	313 x 285 x 454 mm **
	External (inches)	27" x 26.7" x 33.4"	19.1" x 18.7" x 25.5"	12.3" x 11.2" x 17.9"
	Shipping Container (mm)	830 x 830 x 1100 mm	630 x 630 x 920 mm	580 x 440 x 400 mm
	Shipping Container (inches)	32.7" x 32.7" x 43.3"	24.8" x 24.8" x 36.2"	22.8" x 17.3" x 15.7"
Electrical	Voltage	120 V & 220 - 240 V, 50/60 Hz	100 - 120 V & 220 - 240V, 50/60 Hz	100 -120 V & 220 - 240 V, 50/60 Hz
	Power	500 W	500 W	700 W
	Power, High Temp. Option	1000 W	1000 W	N/A
	Consumption to 37°C	< 0.08 kWh	< 0.1 kWh	< 0.06 kWh
Weight	Net	83 kg / 183 lbs	32 kg / 71 lbs	12.5 kg / 28 lbs
	Shipping	100 kg / 220 lbs	50 kg / 110 lbs	18.5 kg / 41 lbs
Warranty	Coverage	Comprehensive 2-year warranty on parts and labor †		
	Maintenance Contracts	Ask your NBS sales representative about our extended maintenance contracts		
Certification	CE Certified			

* Specifications subject to change without notice. All tests performed at ambient temp. of 22°C, the incubator set at 37°C and 5% CO₂. Recovery data follows a 15 second door opening. \emptyset Shelf dimensions are shown wide x deep x high.

** Galaxy 14 S Dimensions are for single unit. When double-stacked, allow 313 x 285 x 887 mm (12.3" x 11.2" x 34.9").

† O₂ sensor has a one year warranty.