



Specification:

	KAFKA SQS date, time and statistic functions
Print	Dual direction thermal print with moveable 8-point head, character constructio: 8 x 8 point matrix, print speed: 0,75 line/s, quantity of signs a line: 40, 80
Set of characters	One from below mentioned: IBM set 2, Mazovia, DHN, Latin-2 PC, Cirylics, Latin-2 ISO
Thermal paper	Roll: width 112 mm, max diameter 42 mm, paper length 20 m, marking: TF 50KS-E2C
Power supply	8,5V - 14V DC or 7V - 10V AC 50Hz, power consumption: 3W - 15W (max.), Power connection: type Jack 2.1, external power adapter: 220V / 9V AC 1,5A 50 Hz
Interface	One from below mentioned: RS232C, RS242 (TTL), RS422A (RS485), power loop 20mA (CL), interface connection: 5 pin type DIN
Transmission parameters	Speed of transmission: 1200, 2400, 4800, 9600 bod (other for seacial order.), transmission protocol: machine with DTR, Data format: 8 or 7 bytes, with or without parity control, parity: even or odd
Durability	MTBF: 5000 hours, MCBF: 500 000 lines
Working conditions	Working temperature: 5°C to 35°C, relative humidity: 10% - 80% (no condensation)
Masses nad dimensions	165 x 140 x 50 mm, 0,45 kg (without paper roll)
Printer marking with set of characters	KAFKA IBM set 2, KAFKA 1 Mazovia, KAFKA 2 DHN, KAFKA 3 Latin - 2 PC, KAFKA 4 Cirylics, KAFKA 5 Latin - 2 ISO
Components	printer, external power adapter, interface plug or cable (according to order), roll of thermal paper, user manual and warranty