

EcoVac *safety-vacuum-system*

Removal of liquid excess



EcoVac

EcoVac
safety-vacuum-system for the
removal of liquid excess

- **autoclavable safety-bottle**
- **low-noise and low-vibration**
double-chambered
membrane pump
- **excellent cost-efficiency**

The EcoVac safety-vacuum-system supports efficient work and increases the safety standard when working with infectious material in a laboratory.

EcoVac easily removes pathogenic liquid excess from dishes, bottles, tubes, disks etc. and transfers to a safety vacuum bottle made of break-resistant and autoclavable polypropylene.

User-friendly concept

EcoVac is a highly functional solution and extremely cost-efficient at the same time.

We recommend a standard pasteur-pipette to remove the excess. It can easily be used with silicone tubing, which connects to the safety vacuum bottle. Further silicone tubing connects the safety vacuum bottle to the vacuum-system, i.e. the vacuum pump or central vacuum.

Safety & Comfort

More safety and comfort

The safety vacuum bottle is resistant to chemicals, has a large capacity and therefore decreases time-consuming autoclaving and disposing to a minimum.

The screw-cap of the bottle comes with two self-locking fittings, which seal the bottle and lock the vacuum bottle hermetically, when the tubing is removed for transport and autoclaving.



The aeration insert ensures the needed pressure equalization when autoclaving.

Space saving

EcoVac only needs a minimum of space in your laboratory. Only the pasteur pipette with the silicone tubing and the vacuum bottle take up work space. By cutting the silicone tubing as needed, the system can easily be adapted to your individual working conditions.

Accessories

Vacuum pump

The vacuum pump is a double-chambered membrane pump with an illuminated on/off-switch.

An optional foot switch allows to control operation of the pump, if EcoVac should be used in intermittently.

Safety filter

The safety filter between the vacuum bottle and the pump prevents the pump from contamination or consequences of aggressive gases or liquids.

Foot-switch

Allows to operate the pump if the EcoVac system should be used intermittently.

Technical Data

Safety vacuum bottle

Capacity	2 or 4 litres
Material	polypropylene
Working temperature (min/max)	0 °C/121 °C

Safety filter

Diameter	62 mm
Housing material	polypropylene
Filter material	Teflon
Pore size	0.2 µm

EcoVac vacuum pump

Double-chambered membrane pump
low-noise and low-vibration
with on/off-switch

Dimensions (w x h x d)	80 x 60 x 160 mm
Weight	approx. 850 g
Max. performance	4 l/min.
Final vacuum	300 mbar
Power	230 V, 50-60 Hz



Ordering Information

EcoVac safety-vacuum-system 2

incl. safety PP-bottle (2 litre)
with screw cap, 2 self-locking fittings,
aeration insert, safety filter and
silicone tubing 5 m (autoclavable)

Cat.-No.

3.350 022

EcoVac safety-vacuum-system 4

incl. safety PP-bottle (4 litre)
with screw cap, 2 self-locking fittings,
aeration insert, safety filter and
silicone tubing 5 m (autoclavable)

3.350 042

Accessories

EcoVac vacuum pump

with connection cable, 1 m

3.350 102

Foot-switch

3.350 202

Safety filter (qty=2)

3.350 302

Glass-pasteur-pipettes, 150 mm (qty=1000)

3.350 402

Glass-pasteur-pipettes, 230 mm (qty=1000)

3.350 502

Replacements

EcoVac replacement safety PP-bottle, 2 litre

3.350 122

EcoVac replacement safety PP-bottle, 4 litre

3.350 142

schuett  **biotec.de**

Rudolf-Wissell-Straße 13, D-37079 Göttingen, Germany

Fon +49 (0) 551/5 04 10-0, Fax +49 (0) 551/5 04 10-99

info@schuett-biotec.de

www.schuett-biotec.de