

WOLF LABORATORIES

Tel: 01759 301142 Fax: 01759 301143 Email: sales@wolflabs.co.uk Website: www.wolflabs.co.uk

GARNET – HG2T

2-Door 2/1 Gastronorm Refrigerator – General Produce



FEATURES

- ? Operating temperature +1°C/+4°C – General Produce Refrigerator
- ? 45cu ft/1273 litres
- ? 430 Stainless steel exterior and 304 stainless steel interior
- ? Easy to clean stainless steel base with radius corners and removable shelf supports and racking
- ? Self closing doors with 140° dwell, barrel lock, magnetic easy clean balloon gasket and curved plastic moulded handles
- ? 150mm heavy duty front and rear swivel and brake castors for easy mobility
- ? 8 shelves fitted as standard or 24 pairs of trayslides to accommodate 2/1 Gastronorm containers
- ? Environmentally friendly 75mm ODP Zero polyurethane foam injected insulation
- ? Top mounted removable refrigeration system for easy service and maintenance
- ? Designed for effective and efficient performance in 43°C ambient environments
- ? State of the art control panel with easy to read LED display for temperature control and diagnostics
- ? Facility to connect to a wide range of temperature monitoring and control systems
- ? HACCP compliant

SPECIFICATIONS:

Capacity: 45 cu.ft/1273 litres

Temperature: +1°/+4°C

External Dimensions: Unpacked: H1970 x W1400 x D824mm

Door Opening: H1370 x W587 x D1477mm

Packed: H2057 x W1475 x D899mm

Internal: H1370 x W1174 x D683mm

Weight: Unpacked: 164kg **Packed:** 169kg

Construction: Exterior: 0.7mm, 430 stainless steel

Top, base and rear are galvanised steel

Door: 0.9mm 430 stainless steel

Interior: 0.7mm, 304 stainless steel walls with radius for easy cleaning

Base: 304 stainless steel, one piece with radiused corners

Door: 0.7mm thick 304 stainless steel door clad

Power Supply: 220-240V supply

50 cycle single phase complete with 13 amp moulded plug

Cabinet Amps: Start-up: 13.4 amps

Running: 3.5 amps

HP: 3/8

Heat Rejection: 37 watts (Evaporating at -10°C in a 32°C ambient). Subject to site conditions and maintenance

Refrigeration: Designed for 43°C ambient with removable sealed system. Automatic off-cycle defrost. Defrost water is vaporised using waste heat from the compressor. Fully automatic air cooled condensing unit.

Refrigerant: R134A

Insulation: 75mm ODP (Ozone Depletion Potential) Zero polyurethane

Internal Fittings: 8 hygienic nylon coated 2/1 GN (W530 x D650mm) wire shelves supported on adjustable anti-tip shelf supports and removable 304 stainless steel ladder racking as standard. Accommodates up to 40 pairs of trayslides for gastronorm trays or shelves.

Sound Rating: 52.6 dBA

Installation: Allow minimum of 500 mm above cabinet for access for maintenance and ventilation. Allow adequate ventilation on all sides of the cabinet to ensure efficient and effective performance.

Options: Glass Doors Extra shelves / trayslides

Half Doors Stainless steel back

Pass Through 304 stainless steel exterior

Helicoil Cable

Adjustable legs (Height increases by 10mm)

Aluminium interior: 0.7mm thick, aluminium walls with radius for easy cleaning

Conversion for Glycol Refrigeration System