



Model: CMRTSS500

500L Solid Door RTS Cabinet

Overview

- +15°C to +25°C temperature range
- Core temperature display, represents your vaccine vial through **iCOOL** INTELLIGENT COOLING temperature probe
- External digital controller and temperature display
- Battery back up
- Annual service & Calibration available
- Fitted lock with 2 keys



1 YEAR PARTS & LABOUR WARRANTY

ANNUAL SERVICE & CALIBRATION AVAILABLE

Key Features



Controller

Controller system. Read, record, reset with the touch of one button. Adjustable temperature setting.



Battery back up

Battery back up should there ever be a power outage the battery backup will continue to monitor the internal temperature of the fridge.



Porthole

Factory fitted porthole enables quick and easy access for any secondary temperature monitoring probes.



LED lighting

Low voltage LED lighting improves running cost as no heat is produced. Long lasting.



Flexible storage

Multiple shelf locations. Back stop on every shelf provides a flexible storage solution.

Details

Model: CMRTSS500

Gross Capacity (litres)	495
Net Capacity (litres)	480
Unit External Width (mm)	1180
Unit External Depth (mm)	600
Unit External Height (mm)	1530
Product Weight (kg)	108
Packed Width (mm)	1230
Packed Depth (mm)	650
Packed Height (mm)	1700
Packed Weight (kg)	119
Temperature Range	+15°C to +25°C
External Finish, Internal Finish	Painted Steel, Painted Steel
Battery Back Up	Yes
Door Finish, Door Type, Door Style	Painted Steel, Solid, 2 Doors Hinged
Open Door Sensor	Yes
Lock	2 Locks, 4 Keys
Adjustable Feet (number)	Lockable Castors (4)
Porthole	Yes
Porthole Location	Rear, Middle
Temperature Display on Panel, Temperature Alarm, Remote Alarm Contacts, Audible Alarms, Visual Alarms	Yes

Number of Shelves	8 (6 full size, 2 base)
Number of Shelf Positions	10+
Shelf Material	Plastic Coated Wire
Interior Light	Yes
Light Type	LED
Light Activation	Switch
Fan	Yes
Spark Free	No
Controller Type	Digital, External
Number of Probes	2
Probe Type	Air & Load
Ambient Temperature Range	+10°C to +30°C
Refrigerant Type	R600a
CFC Free, HCFC Free, Ammonia Free	Yes
Voltage Supply	220-240V/ 50Hz
Certification	CE/UK
Noise Level (dBA)	50
Input Power (W)	380
Cable Length (cm)	20
Energy Consumption (kWh/annum)	3.9

Related Products

**CMRTSG500**500L Glass Door
RTS Cabinet**CMDL01**Advanced Data Logger
with LCD Display**COMBI01**Keyless
Combination Lock



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.