

Biometra TOne
PCR Thermal Cycler



Technical Data

Biometra TOne

General

- Stand-alone control by 7" color touchscreen or remote control by cycler network
- Whisper Quiet with max. 45 dBA
- Small footprint and minimal clearance zone
- Sample block in 96 well format with or without gradient (over 12 columns)
- HPSL technology for ideal constant contact pressure independent of the used consumable
- Suitable for low-profile and high-profile plastic with or without skirt, as well for semi-skirt

Thermal block

Sample block	Aluminum sample block with special alloy
Block capacity	96 x 0.2 ml tubes, 96 well microplates or 8 well strips
Sample size	5 to 50 µl
Block exchange	No
Number of blocks	1
Max. heating ¹	4.0 °C/s
Average heating ¹	3.7 °C/s
Max. cooling ¹	3.3 °C/s
Average cooling ¹	3.0 °C/s
Tempering method	Peltier elements
Standby temperature	Yes, down to 4 °C
Temperature control mode	Block control
Adjustable temperature range	3 °C to 99 °C
Temperature uniformity ²	95°C ± 0.60 °C after 15 sec 70°C ± 0.30 °C after 15 sec 55°C ± 0.20 °C after 15 sec
Temperature control accuracy	± 0.1 °C
Gradient ³	Yes (Semi Linear Gradient Tool)
Max./Min. Gradient ³	20 °C / 0.1 °C
Adjustable gradient range ³	12 columns from 20 °C to 99 °C

¹ measured at cavity wall of the block

² after 15 sec

³ only models with gradient (G)

Technical Data Biometra TOne

Heated lid

Heated lid	High-Precision Smart Lid (HPSL)
Lid temperature	30 °C to 110 °C
Contact pressure	Approx. 8 kg, manual with integrated slip clutch for constant contact pressure independent of the used consumables

Control

Control	Stand-alone or remote control via tablet PC
Control and analysis software	Remote Control App
Operating system	App for iOS or Android
Minimum requirement of PC	iOS 8 or Android 4.0
Language	English, German, Chinese
Display	7" color touchscreen
Export function	Yes
Power fail function	Yes
Quick start function	User-specific quick start
Time inc	1 to 240 sec/cycle
Temperature inc/dec	±0.1 to 20 °C/cycle
Memory capacity	350 programs in up to 90 user directories
Features	<ul style="list-style-type: none"> ▪ Extended Self Test ▪ Graphical or spreadsheet programming ▪ Multip-step programming ▪ Incubation mode ▪ Protocol templates ▪ Program preview

Dimensions

Weight	Approx. 11.5 kg
Dimensions (W x L x H)	260 mm x 430 mm x 241 mm
Required clearance zone	10 cm behind rear side of device. When operating several units side by side, an additional 10 cm between the units.

Technical Data

Biometra TOne

Additional technical data

Interface	<ul style="list-style-type: none">▪ USB-A (front side): connection of an USB memory stick▪ Ethernet (back side): connection to a network
Fuses	2x T 8A H 250 V
Power supply	100 V, 115 V oder 230 V $\pm 10\%$, 50 – 60 Hz
Power consumption	Max. 550 W
Noise emission	Max. 45 dBA
Operation conditions	15 °C to 35 °C, max. 70% humidity, max. 2000 m NN, overvoltage category II, pollution degree 2, IP20
Warranty	2 years warranty on device system

This document is true and correct at the time of publication; the information within is subject to change. Other documents may supersede this document, including technical modifications and corrections.

Content may be used without written permission but with citation of source. © Analytik Jena AG



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed, please provide these to our sales team so that details can be confirmed.

