

## ID-Nr. 30365-001 Model K90.060.110.050.UB.2T



Dimensions	
	1102.00
Width (external)	1102.00 mm
Depth (internal)	380.00 mm
Height (external)	601.00 mm
Width (internal)	470.00 mm
Depth (external)	502.00 mm
Height (internal)	502.00 mm
The available internal dimensions can vary depending on the inte	rior equipment package.
Weight / Load	
Weight without interior equipment	155 kg
Distributed load	275.00 kg/m <sup>2</sup>
Maximum load	300 kg
Ventilation	
Extraction air	50 DN
Minimum exhaust air quantity 10 times	2 m³/h
Differential pressure (10 times air change)	1 Pa
Colouring / Surface finish	
Colouring / Surface finish Body colour code	RAL 7035
	RAL 7035 light grey
Body colour code	
Body colour code Body colour	light grey
Body colour code Body colour Body surface finish	light grey plain
Body colour code Body colour Body surface finish Door / Drawer colour code	light grey plain RAL 7035
Body colour code Body colour Body surface finish Door / Drawer colour code Door / Drawer colour	light grey plain RAL 7035 light grey
Body colour code Body colour Body surface finish Door / Drawer colour code Door / Drawer colour	light grey plain RAL 7035 light grey
Body colour code Body colour Body surface finish Door / Drawer colour code Door / Drawer colour Door / Drawer surface finish	light grey plain RAL 7035 light grey plain
Body colour code Body colour Body surface finish Door / Drawer colour code Door / Drawer colour Door / Drawer surface finish General Information	light grey plain RAL 7035 light grey plain Compartment for the stor
Body colour code Body colour Body surface finish Door / Drawer colour code Door / Drawer colour Door / Drawer surface finish General Information Left compartment	Compartment for the stor age of flammable liquids Compartment for the stor age of flammable liquids Compartment for the storage of aggressive, nor flammable hazardous



## Combi safety storage cabinet K-UB-90 Model K90.060.110.050.UB.2T, light grey (RAL 7035)

Safe and approved storage of aggressive and flammable hazardous substances in working areas

## **Function / construction:**

- Robust construction and longevity: body made of powdercoated sheet steel
- **User-friendly:** access to all containers, 93° opening of the wing door, interior of the cabinet completely visible
- No unauthorised use: doors lockable with cylinder lock and locking state indicator (red/green)
- **Mobile:** castors with plinth (optionally available), easy moving of the cabinet
- **Ventilation:** integrated air ducts ready for connection (DN 50) to a technical exhaust system, extraction of both compartments through one ventilation connection











Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

## www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.