

CAPP Rondo

HIGH SPEED REFRIGERATED CENTRIFUGE



CAPP Rondo High Speed Refrigerated Centrifuge

operates to a maximum speed of 17,000 RPM, corresponding to 27.237 x g. It's an ideal centrifuge for molecular and cellular applications, such as ethanol precipitation, phenol extraction, NA preparation, cell collection or spin-down of temperature-sensitive reaction mixtures.

CAPP Rondo High Speed Refrigerated Centrifuge

offers a maximum rotor capacity of 30 microtubes (18 microfilter tubes or 64 PCR tubes). Its operating temperature range is from -20°C to +40°C. The samples are cooled down to the temperature of 4°C in just 5 minutes. The chamber is rust-free and Teflon-coated. The compressor-off function prevents any unnecessary cooling and frosting while the lid is open.

As with all CAPP Rondo instruments, the High Speed Refrigerated Centrifuge offers quiet operation, keeping the noise level at only 56 dB. The parameters can be changed upon operation unless the Key Lock Function is activated.

CAPP Rondo High Speed Refrigerated Centrifuge

offers multiple rotor options.

Specifications:

Max. RPM / Fixed angle	17,000 RPM	Program memory	100
Max. RCF / Fixed angle	27.237 x g	Parameters on display window	RPM(RCF), Operating Status, Door Open/Close, Min:Sec, Temp, (ACC), (DEC)
Max. capacity / Fixed angle	30 x 1.5 / 2.0mL, 8 PCR strips	Display	Blue LCD
Max. capacity / Swing-out	4 x 4 x 1.5 / 2.0mL	Rotor Identification	Automatic
Temp range (°C)	-20°C to +40°C	Imbalance cutout	Yes
FAST cool button	Yes	Safety lid lock	Yes
Time control	Pulse, timed <100 min, or continuous	Lid drop protection	Yes
Time counting range	Selectable, at set speed or from starting	CE Mark	Yes
RCF/RPM conversion	Yes	Power supply (V/Hz)	200V / 50~60Hz (110V optional)
Noise level	≤56 dB (dependent on rotor)	Power requirement (VA)	2KVA
Acc. time to max. speed	≤17 sec	Dimension (W x D x H)	310 x 620 x 265mm
Dec. time from max. speed	≤15 sec	Weight without rotor	43kg
ACC/DEC ramps	9/10		



CR-17-24

Fixed angle rotor of CR-1730R for 24 x 1.5mL / 2.0mL microtubes. 45°, Hole diameter 11.1mm, Max. height for tube fit 52mm. Supplied with O-ring sealed.

**CR-17-5**

Fixed angle rotor of CR-1730R for 12 x 5mL for screw and snap cap microtubes. 45°, Hole diameter 17mm, Max. height for tube fit 64mm. Supplied with O-ring sealed.

**CR-17-30**

Fixed angle rotor of CR-1730R for 30 x 1.5mL / 2.0mL microtubes. 45°, Hole diameter 11.1mm, Max. height for tube fit 52mm. Supplied with O-ring sealed.

**CR-17-PCR**

Fixed angle PCR-tube Rotor of CR-1730R for 64 x 0.2µL PCR tubes or 8 rows of PCR strips. 45°, Hole diameter 6.5mm, Max height for tube fit 16mm.

CR-17-D8

Drum Rotor of CR-1730R for 8 x 1.5mL / 2.0mL microtubes (buckets are not included) 90°, Hole diameter 11.1mm, Max. height for tube fit 50mm.

**CR-17-18**

Fixed angle rotor of CR-1730R for 18 x 1.5mL / 2.0mL microfilter tubes. 45°, Hole diameter 11.1mm, Max. height for tube fit 65mm. Supplied with O-ring sealed.

**CR-17-D16**

Drum Rotor of CR-1730R for 16 x 1.5mL / 2.0mL microtubes (buckets are not included) 90°, Hole diameter 11.1mm, Max. height for tube fit 43mm.



Ordering Information

Refrigerated Centrifuge

Cat No.	Description
CR-1730R	CAPPRondo Refrigerated Centrifuge 17.000 RPM / 27.237 x g, 220V
CR-1730R-110	CAPPRondo Refrigerated Centrifuge 17.000 RPM / 27.237 x g, 110V

Rotors and accessories for CR-1730R

CR-17-24	Fixed angle rotor of CR-1730R for 24 1.5mL / 2.0mL microtubes
CR-17-30	Fixed angle rotor of CR-1730R for 30 1.5mL / 2.0mL microtubes
CR-17-18	Fixed angle rotor of CR-1730R for 18 microfilter tubes
CR-17-5	Fixed angle rotor of CR-1730R for 12 x 5mL screw and snap cap microtubes
CR-17-PCR	Fixed angle PCR-tube Rotor of CR-1730R for 64 PCR tubes or 8 rows of PCR strips
CR-17-D8	Drum Rotor of CR-1730R for 8 microtubes (buckets are not included)
CR-17-D16	Drum Rotor of CR-1730R for 16 microtubes (buckets are not included)

Buckets for the Rotors of CR-1730R

CR-17-B8	Single tube bucket Drum Rotor CR-17-D8 (total 8 buckets are required)
CR-17-B16	4-tube bucket Drum Rotor CR-17-D16 (total 4 buckets are required)

Buckets for the Rotors of CR-1730R

CR-17-02	0.2mL adaptor of microtube rotors
CR-17-05	0.5mL adaptor of microtube rotors





Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

