



Cleaver

SCIENTIFIC


quickspin



Occupying less than 6 inches square of bench space, the Quickspin has a very small footprint, making it easy to use in the lab. Rotors and adaptors, are supplied as standard to accommodate 1.5 ml, 0.5 ml and 0.4 ml tubes, as well as 0.2 ml strips and tubes. A highly durable stainless steel hinge pin facilitates easy opening of the translucent lid, while an on/off switch is located on the side of the centrifuge to start and stop operation. Alternatively, with the switch in the 'on' position, the centrifuge can be started and stopped by closing and opening the lid.

TECHNICAL SPECIFICATIONS

MAXIMUM SPEED	6000RPM
MAXIMUM G FORCE	2,000 x G
CAPACITY	8 x 1.5/2.0 ML 4 x 0.2 ML STRIPS
UNIT DIMENSIONS (W x L x H)	15 x 15 x 11.6 CM
WEIGHT	1.2 KG
TIME INCREMENTS / DECREMENTS	YES



The Quickspin is perfect for rapid spin-down of sample from the walls and caps of microcentrifuge tubes.

- SUPPLIED WITH BOTH STANDARD MICROTUBE AND STRIPTUBE ROTORS
- IDEAL FOR QUICK SPIN-DOWNS AND MICROFILTRATION
- STARTS AND STOPS IN SECONDS
- COMPACT DESIGN

ORDERING INFORMATION

Cat. No.	Description
CSLQSPINPLUS	Mini Centrifuge complete with 1.5/2.0 ml rotor, strip tube rotor, 0.5 and 0.4 ml adapters, 110V/230V



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.