

THERMALCycler



GTC96S
Thermal Cycler
delivers
exceptional
performance at
an affordable
price




GTC96S Thermal Cycler

- Gene cloning and analysis. Gene expression analysis. Mutational screening
- Compatible with 96-well plates, 0.2ml tubes and tube strips
- Protocol optimization selectable from 1 to 24°C across the entire temperature control range from 4 - 99.9°C
- Precision temperature control increases both speed and efficiency

Faster and with enhanced features, the new GTC96S advanced thermal cycler delivers exceptional performance at an affordable price. An improved protocol optimisation process utilises Flexible Temperature technology to segregate the 96-well plate into six discrete (4x4-well) temperature zones, made easily distinguishable by blue and black squares. Temperature selection is no longer automated and is entirely in the hands of the operator over a 24°C advanced range, anywhere between 4 and 99.9°C. This enables the operator to optimise PCR by testing 6 different temperatures simultaneously in just one thermal cycler run. This is ideal for Genotyping work.

With heating and cooling rates of 5°C/s and 3.5°C/s respectively, the precision temperature control of the GTC96S minimises temperature overshooting and undershooting between individual stages within each PCR cycle, resulting in faster run times and greater efficiency.

Programming is both quick and simple through a large user-friendly interface, while pre-programmed methods for Optimisation, Touchdown and Time Increments make set-up obvious even to first time users. A heated lid, which is fully adjustable to apply optimal pressure to 0.2ml tubes and microplates, may be programmed to hold different temperatures between 60 and 65°C and 100 to 115°C. Additional advantages offered by the new heated lid are its slide-in slide-out design for safe access to samples, and its prevention of condensation formation during overnight cooling.



Flexible temperature technology provides ability to run multiple samples with different annealing temperatures in one run. This is ideal for genotyping.



Intuitive user-friendly interface facilitates manual selection of different temperatures in each of the 4x4-well zones, for full user control during PCR optimisation.



Blue and black squares on the thermal cycler block aid identification of each of the six 4x4-well temperature zones.

TECHNICAL SPECIFICATIONS

| | |
|---|---|
| SAMPLE CAPACITY | 1x 96-WELL PLATE; 12x 8x0.2ML STRIP TUBES; 96 x 0.2ML TUBES |
| PROGRAMMABLE TEMPERATURE RANGE | 4-99.9°C |
| TEMPERATURE CONTROL | CALCULATED OR BLOCK |
| TEMPERATURE ACCURACY / UNIFORMITY | ±0.5°C / ±0.5°C |
| HEATING / COOLING METHOD | PELTIER |
| MAXIMUM HEATING / COOLING RATE | 5°C / 3.5°C PER SECOND |
| TEMPERATURE RANGE OF 6-SEGMENT BLOCKS | 30-99°C; TEMPERATURE OF EACH SEGMENT MAY BE SET INDEPENDENTLY |
| MAXIMUM TEMPERATURE DIFFERENCE BETWEEN 6-SEGMENT BLOCKS | 24°C |
| 6-SEGMENT TEMPERATURE BLOCK FORMAT | 6 SEGMENTS, EACH 4x4-WELL |
| PROGRAMMABLE LID TEMPERATURE | 60-65°C, 100-115°C |
| MEMORY | 200 COMPLETE PROGRAMMES |
| TEMPERATURE INCREMENTS / DECREMENTS | Yes |
| TIME INCREMENTS / DECREMENTS | Yes |

ORDERING INFORMATION

| Cat. No. | Description |
|--------------|--|
| GTC96S | GTC96S thermal cycler with 96-well block, 240VAC |
| CSL-PCRKIT | PCR package includes GTC96S thermal cycler, MSMIDI96 96-well electrophoresis unit and nanoPAC-500 power supply |
| CSL-CLEANCAB | Complete PCR package with low cost clean room. Includes CSL-GTC96S, CSL-UVCAB, CV2, CV20, CV200, CV1000 and CV8-200 pipettes, MSMIDI96 and nanoPAC-500 |



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

