

**Power** 150 W  
**Voltage** 300 V to 3000V (4 versions)  
**Current** 150 mA to 1000mA (4 versions)

**Outputs** 4  
**Operating Modes** 4  
 Simple Mode  
 9x9 Method Programming Mode  
 Voltage Ramp mode  
 Timer Mode (time or Vh)

**USB interface**  
**Datalogging**  
**Real Time Clock**  
**Multiple safety features**  
**Warranty** 36 months  
**Made in Belgium**



## ● Description

EV2000 series is a high-end mid-power range suitable for most applications such as larger tanks or multiple smaller tanks. A robust 150W power supply in a small housing and designed to be easy to use.

The EV2000 series contains 4 different version:

EV2310 (300V, 1000mA): an excellent choice for blotting, multiple horizontal and vertical gels.

EV2650 (600V, 500mA): our most popular all round power supply suitable for most tanks and applications

EV2230 (1500V, 300mA): suitable for higher voltage applications with a need for higher currents

EV2320 (3000V, 150mA): a high voltage power supply in a small form factor suitable for most high voltage applications

The front panel and graphical display are designed for ease of use. The display provides all useful information during runs and will show an on screen help to guide the user in setting up the power supply. In Simple Mode you just have to set your power supply to the desired parameters and press run.

EV2000 series has a firmware upgrade capability so future improvements and features will always be available.

Moreover EV2000 series has a continuous logging combined with a real time clock so it's possible to get an overview of previous runs, including possible down-times in case of mains power failures.

The complete EV series can keep it's voltage constant at low currents without problem and will keep on functioning at low and high temperatures.

Consort Power Supplies are the most robust, long lasting and durable electrophoresis power supplies in the market.

## ● Features

**On screen help** in 4 languages to assist setting up the power supply parameters and solve errors.

**Firmware updates** allows for upgrades to the latest version via the USB interface. Feature requests can also be implemented via the firmware system.

**Real Time Clock** date and time are kept in a battery backup system and is used logging an electrophoresis run.

### **Various running modes:**

**Simple Mode:** just set voltage, current, power and time for a routine electrophoresis run.

**9x9 Method Programming Mode:** Up to 9 different programs, each with 9 steps, can be stored in the non-volatile memory.

Each step is able to recall a next one, providing a flexible multiple step function for special techniques. Parameters of the running step can be changed temporarily without interrupting the run.

**Voltage Ramp Mode:** a linear voltage gradient for any step provided the limiting current or power is not attained.

**Timer Mode:** Timer or volt-hour controlled operation will automatically stop the run and sound an alarm.

**Automatic cross-over** Each model has constant voltage, constant current, constant power capabilities with automatic cross-over and shows which parameter is kept constant.

**Automatic recovery after power failure**

**Password protection**

**Data-logging** Data logging of about 100 hours of runs are automatically stored. Data includes data/time, voltage, current, power and date/time of following events: start, stop, pause, program number, step, changes, mains failure and auto restart.

**Data Transfer** Free data acquisition software for PC can be downloaded from our website. It allows to visualize and examine the stored run details.

**Remote control** EV2000 series can be controlled by a computer using special commands. These commands can be found in the support section of our website.

**Safety features:**

**Ground leakage detection:** protection from potential shock hazard when a ground leakage path is detected.

**Overload protection:** full protection against any overload condition including accidental short circuit of the output.

**Smooth voltage rise:** high voltage cannot suddenly appear at the outputs but will increase smoothly up to the pre-set limits.

**No load detection:** prevents errors such as a bad or a dangling connection.

**Isolated communication:** Optically isolated USB input/output connection to prevent any high voltage on the communication lines.

**Warranty** 3 year warranty on factory faults.

## ● Specifications

	EV2310	EV2650	EV2230	EV2320
<b>VOLTAGE</b>	0...300 V	0...600 V	0...1500 V	0...3000 V
<b>CURRENT</b>	0...1000 mA	0...500 mA	0...300 mA	0...150 mA
<b>POWER</b>	0...150 W	0...150 W	0...150 W	0...150 W
<b>PARAMETER RANGE</b>	1...100% of full scale	1...100% of full scale	1...100% of full scale	1...100% of full scale
<b>TIMER</b>	0...99:59 h	0...99:59 h	0...99:59 h	0...99:59 h
<b>VOLT-HOURS</b>	0...99.99 kWh	0...99.99 kWh	0...99.99 kWh	0...99.99 kWh
<b>DISPLAY</b>	graphical	graphical	graphical	graphical
<b>SETUP RESOLUTION</b>	1 V, 1 mA, 1 W	1 V, 1 mA, 1 W	1 V, 1 mA, 1 W	1 V, 1 mA, 1 W
<b>MEASUREMENT RESOLUTION</b>	1 V, 1 mA, 0.1 W	1 V, 0.1 mA, 0.1 W	1 V, 0.1 mA, 0.1 W	1 V, 1 mA, 0.1 W
<b>PROGRAMS</b>	9x9 set of parameters	9x9 set of parameters	9x9 set of parameters	9x9 set of parameters
<b>OUTPUTS</b>	4 in parallel, 4 mm sockets	4 in parallel, 4 mm sockets	4 in parallel, 4 mm sockets	4 in parallel, 4 mm sockets
<b>MINIMUM LOAD RESISTANCE</b>	10 Ω	30 Ω	300 Ω	600 Ω
<b>NO LOAD DETECTION</b>	✓	✓	✓	✓
<b>GROUND LEAKAGE DETECTION</b>	✓	✓	✓	✓
<b>OVERLOAD DETECTION</b>	✓	✓	✓	✓
<b>COMPUTER CONTROL</b>	✓	✓	✓	✓
<b>PASSWORD PROTECTION</b>	✓	✓	✓	✓
<b>DATA-LOGGING</b>	3600 values	3600 values	3600 values	3600 values
<b>INTERVAL</b>	1...60 seconds	1...60 seconds	1...60 seconds	1...60 seconds
<b>REAL TIME CLOCK</b>	✓	✓	✓	✓
<b>USB INTERFACE</b>	✓	✓	✓	✓
<b>AMBIENT TEMPERATURE</b>	0...40°C	0...40°C	0...40°C	0...40°C
<b>RELATIVE HUMIDITY</b>	0...95%, non condensing	0...95%, non condensing	0...95%, non condensing	0...95%, non condensing
<b>POWER REQUIREMENTS</b>	210-250 VAC, 50/60 Hz, 200 W 100-125 VAC, 50/60 Hz, 200 W	210-250 VAC, 50/60 Hz, 200 W 100-125 VAC, 50/60 Hz, 200 W	210-250 VAC, 50/60 Hz, 200 W 100-125 VAC, 50/60 Hz, 200 W	210-250 VAC, 50/60 Hz, 200 W 100-125 VAC, 50/60 Hz, 200 W
<b>DIMENSIONS (WxDxH)</b>	24x20x13 cm	24x20x13 cm	24x20x13 cm	24x20x13 cm
<b>WEIGHT</b>	6 kg	6 kg	6 kg	6 kg



**Wolflabs**

# Wolf Laboratories Limited

[www.wolflabs.co.uk](http://www.wolflabs.co.uk)

Tel: 01759 301142

Fax: 01759 301143

[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)



**Use the above details to contact us if this literature doesn't answer all your questions.**

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

**The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.**

