



Product Code: EP700G

EcoPro G2 600 Litre Upright Glass Door Refrigerated Cabinet



Features & Benefits

- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet
- Glass door cabinet for easy visibility of stored product, operates up to 32 degrees
- Energy efficiency LED lighting for clear display
- Features Foster's new award-winning +stayclear condenser, revolutionising the effective operation of your refrigeration, ensuring your equipment works more efficiently for longer

Shelving		Base Fittings		Doors	
Additional S/S Trayslides	Option	Remote Refrigeration System	Option	Glass	Standard
Additional GN2/1 Shelf	Option	Castors 80mm	Standard	Left Hand Hinged Door	Option
Refrigeration		Electrical & Service Data		Product Extras	
R290 - Energy Efficient	Standard	230/50/1	Standard	Helicoil Mains Lead	Option
R134a - Industry Standard	Option	220/60/1 Electrical Supply	Option		
Integral Refrigeration System	Standard	Fuse Required (A)	10		
Less Condensing Unit	Option				
Specification		Finish			
Refrigerator +1/+4°C	Standard	s/steel ext, 304 s/s door & alu int	Standard		
Width (mm)	700	304 s/s	Option		
Depth (mm)	820	304 S/S back for island sitting	Option		
Height (mm)	2080				
Unpacked weight (Kgs)	121				
Packed weight (Kgs)	132.6				
Gross Volume (Ltr)	600				
Noise dBA @ 1m	64.9				

Footnotes

- Hydrocarbon option not available on glass door models
- 32° C ambient on glass door refrigerator model
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet



All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

