



Product Code: EP700H

EcoPro G2 600 Litre Upright Refrigerated Cabinet



Features & Benefits

- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet
- Features Foster's new award-winning +stayclear condenser, revolutionising the effective operation of your refrigeration, ensuring your equipment works more efficiently for longer

Shelving	
3 shelves (GN2/1)	Standard
Additional S/S Trayslides	Option
Additional GN2/1 Shelf	Option

Refrigeration	
R290 - Energy Efficient	Standard
R134a - Industry Standard	Option
Integral Refrigeration System	Standard
Less Condensing Unit	Option

Specification	
Refrigerator +1/+4°C	Standard
Width (mm)	700
Depth (mm)	820
Height (mm)	2080
Unpacked weight (Kgs)	121
Packed weight (Kgs)	132.6
Gross Volume (Ltr)	600
Noise dBA @ 1m	68.6

Base Fittings	
Castors 80mm	Standard
Legs 150mm	Option

Electrical & Service Data	
230/50/1	Standard
220/60/1 Electrical Supply	Option
Fuse Required (A)	10
Refrigerant Charge (kg)	0.110

Finish	
s/steel ext, 304 s/s door & alu int	Standard
304 s/s	Option
304 S/S back for island sitting	Option

Doors	
Solid	Standard
Left Hand Hinged Door	Option

Product Extras	
Helicoil Mains Lead	Option

Energy	
kWh (24 hours)	1.24
AEC	452.2383398
Nett Volume	482.3
Energy Grade	B
Global Warming Potential	3
Energy Efficiency Index	32.27

Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet



Application

This appliance is intended for use in ambient temperatures up to {1}°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

