Product Code: EP700H2

EcoPro G2 600 Litre Upright Half Door Refrigerated Cabinet

Features & Benefits

- The half door option is designed to save energy by preventing old air loss during regular use in a hot kitchen
- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet
- Keep accessible products in the top section, bottom half can remain shut for longer preventing cold air loss.

Shelving

Additional S/S Trayslides	Option
Additional GN2/1 Shelf	Option

Base Fittings

Castors 80mm	Standard
Legs 150mm	Option

Doors

Half	Standard
Left Hand Hinged Door	Option

Refrigeration

R290 - Energy Efficient	Standard
R134a - Industry Standard	Option
Integral Refrigeration System	Standard
Less Condensing Unit	Option

Electrical & Service Data

230/50/1	Standard
220/60/1 Electrical Supply	Option
Fuse Required (A)	10
Refrigerant Charge (kg)	0.265

Product Extras

Helicoil Mains Lead	Option

Energy

kWh (24 hours)	1.37
AEC	499.98
Nett Volume	482.3
Energy Grade	C
Global Warming Potential	1430
Energy Efficiency Index	35.68

Specification

Refrigerator +1/+4°C	Standard
Width (mm)	700
Depth (mm)	820
Height (mm)	2080
Unpacked weight (Kgs)	121
Packed weight (Kgs)	132.6
Gross Volume (Ltr)	600
Noise dBA @ 1m	68.6

Finish

s/steel ext, 304 s/s door & alu int	Standard
304 s/s	Option
304 S/S back for island sitting	Option

Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet

Energy Performance Data and information

Application

This appliance is intended for use in ambient temperatures up to {1}°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit our policies

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

Wolf Laboratories Limited

www.wolflabs.co.uk

Wolflabs

Tel: 01759 301142 Fax:01759 301143 sales@wolflabs.co.uk

Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.