



Product Code: EP700H2

EcoPro G2 600 Litre Upright Half Door Refrigerated Cabinet



Features & Benefits

- The half door option is designed to save energy by preventing cold air loss during regular use in a hot kitchen
- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circular II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet
- Keep accessible products in the top section, bottom half can remain shut for longer preventing cold air loss.

Shelving		Base Fittings		Doors	
Additional S/S Trayslides	Option	Castors 80mm	Standard	Half	Standard
Additional GN2/1 Shelf	Option	Legs 150mm	Option	Left Hand Hinged Door	Option
Refrigeration		Electrical & Service Data		Product Extras	
R290 - Energy Efficient	Standard	230/50/1	Standard	Helicoil Mains Lead	Option
R134a - Industry Standard	Option	220/60/1 Electrical Supply	Option	Energy	
Integral Refrigeration System	Standard	Fuse Required (A)	10		
Less Condensing Unit	Option	Refrigerant Charge (kg)	0.265	kWh (24 hours)	1.37
Specification		Finish		AEC	499.98
				Nett Volume	482.3
				Energy Grade	C
				Global Warming Potential	1430
				Energy Efficiency Index	35.68
Refrigerator +1/+4°C	Standard	s/steel ext, 304 s/s door & alu int	Standard		
Width (mm)	700	304 s/s	Option		
Depth (mm)	820	304 S/S back for island sitting	Option		
Height (mm)	2080				
Unpacked weight (Kgs)	121				
Packed weight (Kgs)	132.6				
Gross Volume (Ltr)	600				
Noise dBA @ 1m	68.6				

Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet



Application

This appliance is intended for use in ambient temperatures up to {1}°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

