



Product Code: HR150

Refrigerated Undercounter Cabinet



Features & Benefits

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Roller castors to rear for ease of movement
- Integrated door lock for security
- High quality magnetic door gasket
- Operate to ISO Climate class 4 up to 32°C ambient

Shelving

Nylon Coated Shelf Option

Refrigeration

R600a - Hydrocarbon refrigerant Standard

R134a - Industry Standard Option

Integral Refrigeration System Standard

Finish

s/s ext & alu int Standard

Base Fittings

Castors - Rear Fixed Standard

Levelling Bolts Standard

Electrical & Service Data

230/50/1 Standard

220/60/1 Electrical Supply Option

Fuse Required (A) 10

Refrigerant Charge (kg) 0.065

Energy

kWh (24 hours) 0.82

AEC 247.29

Nett Volume 73.1

Energy Grade A+

Global Warming Potential 3

Energy Efficiency Index 12.51

Doors

Solid Standard

Left Hand Hinged Door Option

Specification

Refrigerator +3/+5°C Standard

Width (mm) 605

Depth (mm) 640

Height (mm) 830

Unpacked weight (Kgs) 69

Packed weight (Kgs) 78.1

Gross Volume (Ltr) 150

Noise dBA @ 1m 68.8

Footnotes

- External cabinet depth excludes 25mm door handle
- Note: for ventilation, ensure that 50mm clearance is allowed above and around the cabinet
- Decibel rating measured 1m high from the floor and 1m from the cabinet



Application

This appliance is intended for use in ambient temperatures up to {1}°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

