

Total gross capacity

Ext. dimensions in mm (w/d/h)

GGU 1550

Premium

Int. dimensions in mm (w/d/h)	474/443/676
Energy consumption in 24 h	0,724 kWh
Climate rating ¹	SN-T
Cooling system	static
Defrosting	manual
Temperature range	-9°C to -26°C
Gastronorm	-
Housing material/colour	stainless steel/stainless steel
Door/lid material	Stainless steel
Liner Material	moulded polystyrol white
Type of control	electronic controller
Temperature display	external digital
Interior light	-
Fault: warning signal	visual and audible
Interface	-
volt-free alarm contact	-
Shelves	4
Adjustable Shelving	-
Number of drawers	-
Number of baskets	4
Maximum number of baskets	4
Shelf material	evaporator plates
Shelf loading	24 kg
leight of adjustable legs	-
Castors/type of castors	-
Door handle	-
oot pedal opener	-
Self-closing door	-
nsulation	-
Defrost water drain	-
Refrigerant	R 600a
Airborne acoustical noise emissions	45 dB(A)
Gross/net weight	42/39 kg
EAN-Nr.	9005382167274

143 litre

600/615/830



N +16°C to +32°C

1 Climate Ratings: **SN** +10°C to +32°C

ST +16°C to +38°C **T** +16°C to +43°C

(



(





Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





