

Genlab

Laboratory Division

LARGE CAPACITY MULTIPURPOSE INCUBATORS



The GENLAB Large Capacity Multipurpose Incubators offer a unique range of highly efficient, reliable and accurate units suitable for much larger applications in incubation, research and general laboratory applications.

Specifications

- Capacities 250 to 1250 Litres
8 sizes vertical style
9 sizes horizontal style
- Temperature range:
ambient + 8°C to 70°C
- Microprocessor digital controller with
dual display of set point and actual
temperature
- Safety overheat thermostat
- 0-99 hour process timer
- 8 segment program (4 ramp 4 dwell)
- Forced convection fan circulation
- Easy clean powder coated body
- Aluminium coated mild steel chamber
- Fitted castors on units 650 litre and above
- Full two year warranty
- C.E. compliant

Options

- Stainless steel chamber
- Inner glass door ('V' style only)
- Fitted castors on units up to 500 litres

Accessories

- Timers/Recorders
- Extraction systems
- Trolleys and racking
- Other accessories available on request



Certificate No. 5531

LARGE CAPACITY MULTIPURPOSE INCUBATORS

Design

The exterior is constructed from sheet steel finished in an easy clean powder coated paint. The interior chamber is made from mild steel coated with aluminium (CLAD) with a stainless steel chamber available as an option.

Fitted with fixed shelf runners and removable chrome plated wire grid shelves.

The vertical style units (V) are fitted with single doors, the horizontal style units (H) are fitted with twin doors.

Heating

Heated by Incoloy sheathed elements positioned in the side fan duct for all units except the 9H and 12H which have a base fan duct.

Controls

The control system comprises of a PID Microprocessor Controller with dual displays of set point and actual temperature, which are auto-tuned for each individual unit to optimise the heat up, overshoot and control of the temperature. They also include mains switch with indicator and heat and overheat indicators.

The controller has a 0-99 hour process timer that can be selected for a fixed time period at a required set point plus an 8 segment program with 4 ramp and 4 dwell facility.

The control panels are fitted on the side of each unit except the 9H and 12H, which are fitted in the base.

Specifications

Horizontal Style (H)

Genlab ref. Number	Capacity (litres)	Internal dims (H x W x D cm)	External dims (H x W x D cm)	No. of shelves	No. shelf positions	Weight (kg)
LCI/9H/DIG	250	54 x 92 x 44	94 x 109 x 57	3	4	80
LCI/12H/DIG	350	54 x 92 x 64	94 x 109 x 77	3	4	120
LCI/15H/DIG	425	76 x 92 x 64	97 x 135 x 81	4	5	150
LCI/18H/DIG	500	91 x 92 x 64	112 x 135 x 81	5	7	165
LCI/22H/DIG	650	91 x 92 x 77	127 x 157 x 95	5	7	180
LCI/27H/DIG	750	106 x 92 x 77	142 x 157 x 95	5	8	200
LCI/30H/DIG	850	122 x 92 x 77	158 x 157 x 95	5	9	220
LCI/35H/DIG	1000	142 x 92 x 77	178 x 157 x 95	5	11	240
LCI/42H/DIG	1250	142 x 122 x 74	178 x 187 x 92	5	11	275

Vertical Style (V)

Genlab ref. Number	Capacity (litres)	Internal dims (H x W x D cm)	External dims (H x W x D cm)	No. of shelves	No. shelf positions	Weight (kg)
LCI/9V/DIG	250	91 x 51 x 52	117 x 94 x 61	5	7	85
LCI/12V/DIG	350	91 x 61 x 62	117 x 104 x 79	5	7	110
LCI/15V/DIG	425	91 x 61 x 77	117 x 104 x 94	5	7	140
LCI/18V/DIG	500	114 x 61 x 77	140 x 104 x 94	5	9	155
LCI/22V/DIG	650	114 x 77 x 77	150 x 142 x 95	5	9	170
LCI/27V/DIG	750	128 x 77 x 77	164 x 142 x 95	5	10	190
LCI/30V/DIG	850	142 x 77 x 77	178 x 142 x 95	5	11	210
LCI/35V/DIG	1000	142 x 77 x 92	178 x 142 x 110	5	11	230



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

