

Polymax 1040 (5° tilt angle)



The incubating model

- The Polymax 1040 is a medium-sized model and accepts load capacities of 5 kg
- Model with a tilt angle of 5° for soft and gentle movements
- Use this model for any vessel – from culture plates and media bottles to Erlenmeyer flasks – there is no limit
- Set and continuously adjust the variable speed on the analog control knob from 2 to 50 rpm – ideal for cell culture plates
- This model is suitable for the modular incubator system and is recommended for applications which require variable temperature control up to 65 °C
- An analog process timer allows for unattended operation and can be set from 1 to 120 minutes. When the set time has elapsed an acoustic alarm will sound and the operation stops

Polymax 1040 (5° tilt angle) - Technical Data

Overheat protection	self-resetting
Permissible ambient conditions	5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing linearly up to max. 50 % rel. humidity
Weight	8 kg
Protection class DIN EN 60529	IP 40
Timer	1
Rotation speed range	2 - 50 rpm
Power input	115 W
Dimensions (w/d/h)	320 x 375 x 195 mm
Max. Load	5 kg
Operating Mode	timer or continuous
Rotation speed setting	electronic control
Orbit / Stroke	-
Platform size	290 x 258 mm
Accessories included	non-skid rubber mat
Angle	5°
Motion	wave



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

