
Hei-VAP Advantage - hand lift model with G6 vertical glassware



With the Hei-VAP Advantage rotary evaporator you have a direct view on all parameter settings and are able to expand your application range

- Experience the advantages of our large digital 3.5" LCD display which indicates rotation speed, heating bath and vapor temperature
- The automatic process timer turns off your evaporator at a preprogrammed time
- Hei-VAP Advantage hand lift model with G6 vertical glassware for reflux distillation
- Hei-VAP Advantage models can be upgraded to a Hei-VAP Precision with the optional Upgrade-KIT Advantage Precision

Intelligent evaporation with Heidolph rotary evaporators: overheat protection design that prevents water baths running dry, provides a detachable panel for superior ease of use from outside closed fume hoods and offers a proven vacuum seal and vapor tube system guaranteed for years of operation!



Hei-VAP Advantage - Technical Data

| Rotation speed indicator | 3.5" LCD Display |
|--|---|
| Permissible ambient conditions | 5 – 31 °C at 80 % rel. humidity 32 – 40 °C decreasing lineary up to max 50% rel. humidity |
| Protection class DIN EN 60529 | IP 20 |
| Lift | Hand lift |
| Height adjustment speed | manual |
| Height adjustment | 155 mm |
| Drive | brushless DC motor with electronic speed control |
| Heating capacity | 1,300 W |
| Temp. range heating bath | 20 - 210 °C |
| Temperature accuracy bath | ±1 °C |
| Overheat protection bath | cut-off at 5 °C over set temperature via separate PT 1000 |
| Bath temperature setting | 3.5" LCD Display |
| Heating bath temperature control | electronic / digital |
| Secondary overtemp. cut off | 250 °C |
| Material heating bath | stainless steel AISI 316L |
| Diameter heating bath | 255 mm |
| Volume heating bath | 4.5 |
| Display vapor temperature | yes |
| Required accessories for display vapor temperature | vapor temperature sensor |
| Integrated vacuum controller | - |
| Timer | yes |
| Vacuum program SETpressure | - |
| Vacuum program AUTOeasy | - |
| Vacuum program AUTOaccurate requires | - |



Premium Laboratory Equipment

AUTOaccurate sensor

| Programmable ramps | - |
|---|--------------------------------------|
| Supply Power | 1,400 W |
| Weight without glassware assembly | 16 kg |
| Dimensions with glassware set G3 (w/d/h) | 477 mm x max. 739 mm x 845 mm |
| Dimensions with glassware set G3 XL (w/d/h) | 477 mm x max. 739 mm x 920 mm |
| Condensing surface | 1,400 cm ² |
| Condensing surface XL condenser | 2,200 cm ² |
| Max. size evaporating flask | 5 |
| Display | yes 3.5" LCD Display |
| Rotation speed range | 10 - 280 rpm |
| Remote control function | Start Rotation Start heating bath |





Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





