

## Unimax 2010



### The resilient model

- The Unimax 2010 is a large model and accepts a load capacity of 10 kg for high sample throughput
- The shaking orbit of 20 mm performs a gentle motion for sensitive samples and supports culture plates and Erlenmeyer flasks
- Set and continuously adjust the variable speed on the digital display from 20 to 400 rpm
- Increase your sample throughput with the optional multi-tier attachment for a variety of vessel sizes
- An analog process timer allows for unattended operation and can be set from 1 to 120 minutes. When the set time has elapsed an acoustic alarm will sound and the operation stops

## Unimax 2010 - Technical Data

Overheat protection	self-resetting
Permissible ambient conditions	5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing linearly up to max. 50 % rel. humidity
Weight	16 kg
Protection class DIN EN 60529	IP 20
Timer	1
Rotation speed range	20 - 400 rpm
Power input	115 W
Dimensions (w/d/h)	426 x 435 x 135 mm
Max. Load	10 kg
Operating Mode	timer or continuous
Rotation speed setting	digital
Orbit / Stroke	20 mm
Platform size	390 x 340 mm
Accessories included	non-skid rubber mat
Angle	-
Motion	orbital



**Wolflabs**

# Wolf Laboratories Limited

[www.wolflabs.co.uk](http://www.wolflabs.co.uk)

Tel: 01759 301142

Fax: 01759 301143

[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)



**Use the above details to contact us if this literature doesn't answer all your questions.**

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

