

Vibramax 110



The efficient model

- Ideal for the optional attachment to use 49 test tubes that increases your throughput significantly
- The shaking orbit of 1.5 mm performs a gentle motion for sensitive samples
- Set and continuously adjust the variable speed on the analog control knob from 150 to 2,500 rpm
- An analog process timer allows for unattended operation and can be set from 1 to 120 minutes. When the set time has elapsed an acoustic alarm will sound and the operation stops

Vibramax 110 - Technical Data

Overheat protection	self-resetting
Permissible ambient conditions	5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing linearly up to max. 50 % rel. humidity
Weight	12.2 kg
Protection class DIN EN 60529	IP 30
Timer	1
Rotation speed range	150 - 2,500 rpm
Power input	46 W
Dimensions (w/d/h)	245 x 310 x 146 mm
Max. Load	2 kg
Operating Mode	timer or continuous
Rotation speed setting	electronic control
Orbit / Stroke	1.5 mm
Platform size	140 x 140 mm
Accessories included	non-skid rubber mat
Angle	-
Motion	vibrating



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

