



designed for scientists



## **IKA Pette vario 1-10 ml**

/// Data Sheet

An ergonomic feel combined with uncompromising precise performance: the IKA single fix and vario pipettes can be used for many applications in the modern laboratory. Colour coding simplifies the rapid selection of a suitable pipette. Resistance to impact, UV and chemicals ensures that the tip cone provides long-term reliable dosing. The PETTE fix and vario are fully autoclavable, therefore ensuring easy sterilization. This guarantees fault-free, precise and safe operation.

### **Ergonomic design**

IKA pipettes are delivered including exchangeable grips in different shapes and materials. Therefore it is guaranteed



designed for scientists

that they fit well in the palm of the hand. The minimal frictional and spring forces also ensure dosing with ergonomic handling; without any effort.

One-handed adjustment of the volume is possible using the multifunctional knob. Moreover, the pipette tip can be released, regardless of the hand position, while the volume adjustment is securely locked.

#### Durable construction

This combination guarantees particularly robust pipettes and reliably meter day by day in the long term.

#### A large display

The display shows the set volumes in easily read characters. The deep position also allows reading while pipetting, without changing the hand position.

#### User-friendly calibration

The IKA software used for planning, performing and recording calibration tests for PETTE fix and vario is particularly user-friendly.

#### Simple maintenance and adjustment

The volume unit with piston and seal can be disassembled and cleaned in just a few simple steps. If adjustment is necessary, it can be done without any additional tool.



designed for scientists

## Technical Data

|   |  |
|---|--|
| Design  | Air displacement piston-operated pipette |
| Handling  | mechanical                               |
| Volume  | variable                                 |
| Number of channels                              | 1  |
| Colour Code                                     | Red                                      |
| Nominal volume [μl]                             | 10000                                    |
| Volume min. [μl]                                | 1000                                     |
| Volume max. [μl]                                | 10000                                    |
| Increments [μl]                                 | 10                                       |
| Accuracy with nominal volume [±μl]              | 60                                       |
| Accuracy with nominal volume [±%]               | 0.6                                      |
| Precision with nominal volume [±μl]             | 15                                       |
| Precision with nominal volume [±%]              | 0.15                                     |
| Accuracy with 50% of nominal volume [±μl]       | 40                                       |
| Accuracy with 50% of nominal volume [±%]        | 0.8                                      |
| Precision with 50% of nominal volume [±μl]      | 10                                       |
| Precision with 50% of nominal volume [±%]       | 0.2                                      |
| Accuracy with 10% of nominal volume [±μl]       | 30                                       |
| Accuracy with 10% of nominal volume [±%]        | 3  |
| Precision with 10% of nominal volume [±μl]      | 6  |
| Precision with 10% of nominal volume [±%]       | 0.6                                      |
| Certificate of conformity according to ISO 8655 | yes                                      |
| Autoclavable                                    | yes                                      |
| Dimensions (W x H x D) [mm]                     | 30 x 222 x 63                            |
| Weight [kg]                                     | 0.108                                    |
| Permissible ambient temperature [°C]            | 5 - 40                                   |
| Permissible relative humidity [%]               | 90                                       |



**Wolflabs**

# Wolf Laboratories Limited

[www.wolflabs.co.uk](http://www.wolflabs.co.uk)

Tel: 01759 301142

Fax: 01759 301143

[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)



**Use the above details to contact us if this literature doesn't answer all your questions.**

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

