



designed for scientists



RV 10 auto FLEX

/// Data Sheet

The completely revised RV 10 auto is the flagship of the IKA Rotation Evaporator product line. Its impressive features include an innovative control concept with a bright, high-contrast, TFT, color-graphic control panel, an integrated vacuum controller, cooling water monitoring and mature safety standards. The RV 10 auto offer all properties required for efficient, safe, and cost-effective operations. These include automatic control of the vacuum and cooling water volume. Its intuitive handling concept quickly leads its users to their desired results in every application. Thanks to its extended ramp programming capability, the RV 10 auto allows users to carry out customized procedures. Other innovative features, such as smooth start, interval mode, right-left operation in interval mode, or the timer function for time-lapse tests, make everyday work in the laboratory much easier. Safety is ensured by the motorized lift with



designed for scientists

safety-stop function that automatically lifts the evaporation flask out of the heating bath in the case of power failure. Additional safety for users is provided by individually adjustable temperature safety circuits, protection against boiling dry, adjustable end-point recognition to prevent glass breakage, and a locking function. The receiving flask and the condenser are also available in coated versions. The USB port or the RS-232 interface enable remote control with the IKA "labworldsoft" software package and an update option with the firmware update tool. The device comes complete with vacuum hoses and hose connectors for your in-house cooling water supply.

- New: 4 l heating bath
- integrated vacuum controller
- integrated solvent library with 40 preset solvents and expansion option
- bright, high-contrast, TFT, color-graphic control panel
- universal safety heating bath
- optimized heating bath volume for rapid achievement of working temperature
- heating bath with ergonomic handles
- temperature safety circuit
- boil-dry protection
- intuitive handling concept with simple menu navigation
- programming option for up to ten individual procedures
- smooth start
- right or left rotation
- timer function
- end-point recognition
- push-off mechanism for tightly-fitting flasks
- digital interfaces: USB port and RS-232 interface for remote control
- multi-language operating system
- automatic cooling water management
- automatic ventilation
- automatic heating bath management



designed for scientists

Technical Data

| | |
|--|--------------------|
| Type of cooling | Vertical condenser |
| Cooling surface [cm ²] | 1500 |
| Speed range [rpm] | 5 - 300 |
| Reversible direction of rotation | yes |
| Speed tolerance set rotation speed < 100rpm [±rpm] | 1 |
| Speed tolerance set rotation speed > 100rpm [±%] | 1 |
| Lift | Motor |
| Stroke [mm] | 140 |
| Heating temperature range [°C] | room temp. - 180 |
| Heat output [W] | 1350 |
| Set temperature resolution [±K] | 1 |
| Filling volume max. [l] | 4 |
| Vacuum controller integrated | yes |
| Timer | yes |
| Dimensions (W x H x D) [mm] | 500 x 430 x 440 |
| Weight [kg] | 18.6 |
| Permissible ambient temperature [°C] | 5 - 40 |
| Permissible relative humidity [%] | 80 |
| Protection class according to DIN EN 60529 | IP 20 |
| RS 232 interface | yes |
| USB interface | yes |
| Analog output | yes |
| Voltage [V] | 100 - 240 |
| Frequency [Hz] | 50/60 |
| Power input [W] | 100 |
| Power input standby [W] | 3.3 |



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

