





The new RV 3 Rotary Evaporator is the ideal entry-level model of the IKA rotary evaporator portfolio. It finds a multitude of uses in the chemical, pharmaceutical, and biotechnology industries, in research and development, in manufacturing and quality assurance, in laboratories, and in plant construction. Thanks to specially designed glass guides, the transparent vertical coated condenser makes extremely efficient use of the 1500 cm² cooling surface.

IKAworldwide

- New: 4 I heating bath for up to 99°C
- water heating bath with digital temperature display and carrying handles
- mechanical lift end-point safety stop



- locking mechanism: red indicator shows unlocked position of the vapor tube
- manual lift for precise positioning of the glassware
- adjustable immersion angle
- single-handed manual lift handling, suitable for left and right-handed operators
- stepless speed setting with dial control and speed display
- speed range: 20-300rpm
- low device voltage (24V) ensures user safety
- flask clamping mechanism with integrated push-off function for easy exchange of evaporation flasks
- high-efficiency condenser with 1500 cm² cooling surface low space requirements
- compatible with the entire range of IKA RV 10 glassware



Technical Data

20 - 300	
scale	
1	
1	
manual	
150	
440 x 530 x 330	
22.31	
5 - 40	
80	
IP 20	
100 - 240	
50/60	
75	
	scale 1 1 100 440 x 530 x 330 22.31 5 - 40 80 IP 20 100 - 240 50/60



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





