



ROCKER 3D digital

/// Data Sheet

Digital shaker with three-dimensional tumbling motion and adjustable speed for smooth mixing tasks. Used for homogeneous mixing in flasks, culture flasks, Petri dishes and tubes. Ideal for e.g. the cultivation of cell cultures, DANN extractions, distributing of cells and staining and destaining of cells. Even with load and voltage fluctuations, shaking speed remains constant. An adjustable angle ensures optimum adaption to the particular experimental conditions.

- Timer: Countdown, adjustable from 1 s to 99h 59min
- Counter: Display of shaking time
- Error Code Display



- Different attachments enable use for a variety of applications
- Usable at 4 to 50 °C in incubators
- Easy operation with touch keypad
- Anti-slip rubber mat included
- Suitable for continuous operation
- Shaking diameter: 0 15° (angle)
- Speed range: 5 80 rpm



Technical Data

Type of movement	tumbling	
Permissible shaking weight (incl. attachment) [kg]	2	
Permissible ON time [%]	100	
Speed min (adjustable) [rpm]	5	
Speed range [rpm]	0 - 80	
Speed display	7 segment LED	
Speed control	1 RPM steps	
Timer	yes	
Timer display	7 segment LED	
Time setting min. [s]	1	
Time setting max. [min]	5999	
Operating mode	timer and continuous operation	
Tumbling angle adjustable [°]	0 - 15	
Shaking platform stackable	yes	
Altitude (when shaking platform stacked) [mm]	30	
Dimensions (W x H x D) [mm]	280 x 185 x 330	
Weight [kg]	2.3	
Permissible ambient temperature [°C]	4 - 50	
Permissible relative humidity [%]	80	
Protection class according to DIN EN 60529	IP 21	
Voltage [V]	100 - 240	
Frequency [Hz]	50/60	
Power input [W]	24	
DC Voltage [V=]	24	
Current consumption [mA]	1000	



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





