



designed for scientists



ROLLER 10 digital

/// Data Sheet

Digital roller shaker with 10 rolls provides smooth rocking and rolling action at infinitely adjustable speeds. Used for mixing blood samples, solid and liquid suspensions and viscous samples. The unit can be used with all conventional tubes and cylindrical bottles. Easily removable attachments provide for quick cleaning in case of sample spills.

- Timer: Countdown, adjustable from 1 s to 99h 59min
- Counter: Display of shaking time
- Error Code Display
- Usable at 4 to 50 °C in incubators



IKAworlwide



IKAworlwide /// #lookattheblue



@IKAworlwide



designed for scientists

- Suitable for continuous operation
- Removable rolls enable shaking of larger tubes
- Easy operation with keypad
- Shaking diameter: 24,5 mm (height)
- Speed range: 5 - 80 rpm



IKAworlwide



IKAworlwide /// #lookattheblue



@IKAworlwide



designed for scientists

Technical Data

Type of movement	rolling
Permissible ON time [%]	100
Speed min (adjustable) [rpm]	5
Speed range [rpm]	0 - 80
Speed display	7 segment LED
Speed control	1 RPM steps
Timer	yes
Timer display	7 segment LED
Time setting min. [s]	1
Time setting max. [min]	5999
Operating mode	timer and continuous operation
Rolls, number	10
Rolls, Ø [mm]	32
Rolls, length [mm]	327
Working area length [mm]	350
Rolls, luffing angle fixed [°]	3
Rolls, max stroke at roll end [mm]	16
Rolls, changeable, removable	yes
Dimensions (W x H x D) [mm]	380 x 115 x 545
Weight [kg]	6
Permissible ambient temperature [°C]	4 - 50
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 21
Voltage [V]	100 - 240
Frequency [Hz]	50/60
Power input [W]	24
DC Voltage [V=]	24
Current consumption [mA]	1000





Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

