



HS 260 control

/// Data Sheet

The HS 260 control open air reciprocating shaker is a reliable and efficient solution for laboratory applications that require gentle mixing of samples. It has a compact and flat design, making it easy to fit into any lab space. With a maximum shaking weight of 7.5 kg, it can handle a variety of vessel sizes and shapes. The shaker's integrated end point positioning function is highly useful for automated robot-controlled sampling.

- Digital LED display makes it easy to read the speed and timer function
- Speed and timer can be electronically adjusted for precise control
- Shaking orbit of 10.0 mm, which ensures consistent mixing and good oxygen input
- Variable speed range of 10-300 rpm, making it suitable for a wide range of applications
- Timer function (from 1 min to 99 h 59 min) and continuous operation available



- RS 232 interface for external control and documentation through labworldsoft®
- Wide range of attachment combinations available, allowing users to use almost all shapes and sizes of vessels,
- accessories are not part of the scope of delivery and have to be ordered separately
- A special version with clockwise and anticlockwise rotation is available upon request



Technical Data

| Type of movement | reciprocating |
|--|--------------------------------|
| Shaking stroke [mm] | 20 |
| Permissible shaking weight (incl. attachment) [kg] | 7.5 |
| Motor rating input [W] | 45 |
| Motor rating output [W] | 10 |
| Permissible ON time [%] | 100 |
| Speed range [rpm] | 10 - 300 |
| Speed display | LED |
| Timer | yes |
| Timer display | LED |
| Time setting range [min] | 1 - 5999 |
| Operating mode | timer and continuous operation |
| Shaking table lock | yes |
| Dimensions (W x H x D) [mm] | 360 x 100 x 420 |
| Weight [kg] | 8.8 |
| Permissible ambient temperature [°C] | 5 - 50 |
| Permissible relative humidity [%] | 80 |
| Protection class according to DIN EN 60529 | IP 21 |
| RS 232 interface | yes |
| Analog output | yes |
| Voltage [V] | 220 - 240 |
| Frequency [Hz] | 50/60 |
| Power input [W] | 45 |
| Fuse | 2x T1A 250V |





www.wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all

your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed, please provide these to our sales team so that details can be confirmed.

