



### KS 260 basic

/// Data Sheet

Compact, flat orbital shaker with ideal swivel motion, for a maximum shaking weight of 7.5 kg.

- Electronic adjustment of speed and timer
- LED display for speed and time adjustment
- Wide range of attachment combinations makes it possible to use almost all shapes and sizes of vessels
- Attachments are not included, please order separately



#### **Technical Data**

Type of movement	orbital	
Shaking stroke [mm]	10	
Permissible shaking weight (incl. attachment) [kg]	7.5	
Motor rating input [W]	45	
Motor rating output [W]	10	
Permissible ON time [%]	100	
Speed min (adjustable) [rpm]	50	
Speed range [rpm]	0 - 500	
Speed display	LED line	
Timer	yes	
Timer display	LED line	
Time setting range [min]	5 - 50	
Operating mode	timer and continuous operation	
Dimensions (W x H x D) [mm]	360 x 98 x 420	
Weight [kg]	8.5	
Permissible ambient temperature [°C]	5 - 50	
Permissible relative humidity [%]	80	
Protection class according to DIN EN 60529	IP 21	
Analog output	yes	
Voltage [V]	220 - 240 / 100 - 120	
Frequency [Hz]	50/60	
Power input [W]	45	



## **Wolf Laboratories Limited**

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk



# Use the above details to contact us if this literature doesn't answer all your questions.

# Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





