

designed for scientists



C-MAG HS 10

/// Data Sheet

Magnetic stirrer with heating and ceramic heating plate which offers excellent chemical resistance.

- Powerful motor for stirring quantities of up to 15 I (H2O)
- Fixed safety circuit of 550 °C
- Hot Top indicator >> hot surface warning to prevent burns!
- Exact temperature setting via digital display (LED)
- Bushing according to DIN 12878 for connecting a contact thermometer, e.g. ETS-D5, enables precise temperature control
- Digital error code display
- Elevated control panel for protection against leaking liquids



Technical Data

Number of stirring positions	1	
Stirring quantity max. per stirring position (H2O) [I]	15	
Motor rating output [W]	1.5	
Direction of rotation	left	
Speed control	scale 0 - 6	
Speed range [rpm]	100 - 1500	
Stirring bar length max. [mm]	80	
Heat output [W]	1500	
Heating temperature range [°C]	50 - 500	
Heat control	LED	
Heating rate heating plate [K/min]	5	
Connection for ext. temperature sensor	ETS-D5	
Fixed safety circuit [°C]	550	
Set-up plate material	ceramic	
Set-up plate dimensions [mm]	260 x 260	
Dimensions (W x H x D) [mm]	300 x 105 x 415	
Weight [kg]	6	
Permissible ambient temperature [°C]	5 - 40	
Permissible relative humidity [%]	80	
Protection class according to DIN EN 60529	IP 21	
Voltage [V]	230 / 120 / 100	
Frequency [Hz]	50/60	
Power input [W]	1520	



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





