

General Purpose Trolleys

This extensive range of general purpose trolleys is of fully welded construction, with tubular end frames. Overall 1060mm long x 460mm wide x 950mm high including 100mm diameter swivel castors. The work surface, base and intermediate shelves can be supplied with edges lipped down if required (to be specified at time of ordering). Sky Blue (RAL 5015).

Trolleys

L x W x H (mm)	Code
1060 x 460 x 950	GP1
1060 x 460 x 950	GP2
1060 x 460 x 950	GP3
1060 x 460 x 950	GP4
1060 x 460 x 950	GP5

As Standard

All trolleys are supplied with all swivel 100mm nylon castors offering a carrying capacity of 200kg (UDL). Rubber tyred castors offer a capacity of 150kg (UDL).

Shelves

Trolley shelves are supplied lipped up 30mm as standard to all 4 sides except GP5 which are lipped down.

Colour Options

Supplied in Sky Blue (RAL 5015) with cabinet doors in Light Grey (RAL 7035), other options available.

Options & Accessories (Factory Fitted)

Description	Code
Braked Castors (pair)	BC
Rubber Mat	RM
Plastic Tray	PT
Rubber Tyred Castors	RTC



Plastic Tray - 25kg UDL



Rubber Mat



Rubber Tyre Castors (150kg UDL)



Fully welded all steel 2 tier trolley
Order code: GP1



Fully welded all steel 3 tier trolley
Order code: GP3



Fully welded all steel 2 tier trolley
with double drawer
Order code: GP2



Fully welded 2 tier all steel trolley
with triple drawer and cabinet
Order code: GP5



Fully welded all steel 2 tier trolley
with double doors
Order code: GP4



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

