

## Jeio Tech 5 to 100rpm Rocking Shaker (CRS-350)

**Product Code:** AAH391115K

**Brand:** Jeio Tech

The Jeio Tech 5 to 100rpm Rocking Shaker (CRS-350) comes with an adjustable tilt angle and precise digital speed control, providing a desirable rocking motion.

Three different detachable trays for this laboratory shaker can be used to efficiently transfer well-plates and test tubes in various sizes.



## Features

### Performance

- Microprocessor PID control
- Digital speed control providing gentle to vigorous motion (5 to 100rpm)
- Easy to adjust tilt angle (7 to 13°)
- Smooth, quiet, uniform, and yet powerful shaking motion

### Convenience

- Vivid and colourful fluorescent display (VFD) with touch-sensitive keypad
- One-touch timer for time-dependent shaking operation (1 min. to 99 hr. 59 min.)
- Three types of removable tray for easy transport of well-plates, test tubes, etc. (standard dimpled mat, and optional rubber mat and universal harness)
- Variety of accessories are available to meet application demands. Accommodates to be used in a variety of test tube size, beakers, vials, micro well-plates, culture dishes, plastic/glass trays

### Safety

- Self-diagnostic function identifying errors
- Its polypropylene main body is highly chemical-resistant and easy-to-clean
- Over-current protection

## Specifications

<b>Control System</b>	PID feedback control
<b>Display</b>	VFD
<b>Motion</b>	Rocking
<b>Speed Range (rpm)</b>	5 to 100
<b>Tilt Angle</b>	7 to 13°
<b>Max. Load (kg)</b>	5
<b>Tray Dimensions (W x D)</b>	276 x 276mm
<b>Dimensions (W x D x H)</b>	249 x 325 x 138mm
<b>Weight (kg)</b>	3.7



**Wolflabs**

# Wolf Laboratories Limited

[www.wolflabs.co.uk](http://www.wolflabs.co.uk)

Tel: 01759 301142

Fax: 01759 301143

[sales@wolflabs.co.uk](mailto:sales@wolflabs.co.uk)



**Use the above details to contact us if this literature doesn't answer all your questions.**

**Pricing on any accessories shown can be found by keying the part number into the search box on our website.**

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

