

4510

Bench Conductivity/TDS Meter

The 4510 is easy to use but with the flexibility to meet the broadest range of applications and for those where greater accuracy is required the 4510 has automatic conductivity standard recognition and endpoint detection. Set-up options include cell constant, temperature coefficient and reference temperature. The instrument can store up to 32 readings, which can also be sent to a printer or transferred to computer via DataWay and the RS232 interface.

Technical Specification

Conductivity

| | |
|----------------------------|---------------------------------------|
| Range | 6 auto-selected from 0 to 19999mS* |
| Resolution | 0.01µS to 1mS |
| Accuracy | ±0.5% ±2 digits |
| Automatic std. recognition | 10µS, 84µS, 1413µS, 12.88mS |
| Cell constant | 0.010 to 19.999 |

TDS

| | |
|------------|--------------------------------|
| Range | 6 auto-select from 0-19999g/l* |
| Resolution | 0.01mg/l to 1g/l |
| Accuracy | ±0.5% ±2 digits |
| EC Ratio | 0.50 to 0.80 |

Temperature

| | |
|-------------------------|------------------------|
| Range | -10 to 105°C |
| Resolution | 0.1°C |
| Accuracy | ±0.5°C |
| ATC and manual | 0 to 100°C |
| Temperature coefficient | 0.00% to 4.00%/°C |
| Reference temperature | 18, 20 or 25°C |
| Outputs | Analogue and RS232 |
| Connector | 7-pin DIN |
| Power | 9V AC ±10% @ 50/60Hz** |
| Size (l x w x d), mm | 210 x 250 x 55 |
| Weight, g | 850 |

Key Features

- Simultaneous display of conductivity or TDS and temperature
- Automatic selection of range for best resolution
- Calibration by cell constant or standard solutions
- Automatic standard recognition
- Storage of up to 32 results
- Bi-directional RS232 link to printer or PC



4510

Part code: 451 001

Ordering Information

| Part Code | Description |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| 451 001 | 4510 conductivity meter supplied with glass conductivity probe with ATC (K=1) (027 013), electrode holder (903 300) and UK power supply (021 030) |

*With K=10 cell

** Voltage variants available see page 94





Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

