


Precision balances KERN PLS · PLJ



STANDARD



EasyTouch



1



2



A



C

Technical data

- Backlit LCD display, digit height 15 mm
- Dimensions weighing surface, stainless steel
 - A Ø 110 mm
 - B Ø 160 mm, see larger picture
 - C W×D 200×175 mm
- Permissible ambient temperature
KERN PLS, PLJ: 5 °C/35 °C, 35 °C
KERN PLJ-M: 15 °C/30 °C

High-quality precision scale with comfortable graphic display and enormous weighing range

Features


- Rapid and efficient operation thanks to the graphics display
- 1 Convenient recipe-weighing: with the recipe database, in which up to 99 recipes can be stored, each with up to 20 recipe ingredients with name and target value
- Simple, clear user interface on the display in the following languages: German, English, French, Italian, Spanish, Portuguese
- 2 KERN PLJ 2000-3A: High-quality milligram balance with enormous weighing range up to 2100 g – ideal for large samples or heavy tare containers

- KERN PLJ: Automatic internal adjustment, guarantees high degree of accuracy and makes the balance independent of its location of use. Ideal for mobile applications which require verification, such as ambulatory gold and jewellery purchasing
- Dosage aid: high stability mode and other filter settings can be selected
- Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display
- Draught shield standard for models with weighing plate size A, weighing space Ø×H 150×60 mm
- Protective working cover included with delivery

Accessories

- Protective working cover, scope of delivery: 5 items, KERN PLJ-A01S05
- 3 Hook for underfloor weighing, KERN PLJ-A02
- Set for density determination of liquids and solids with density > 1 for models with [d] = 0,001 g, KERN ALT-A02
- Minimum weight of sample, smallest weight to be weighed, depending on the required process accuracy, only in combination with a DAkkS calibration certificate, KERN 969-103
- Equipment qualification: compliant qualification concept which includes the following validation services: Installation Qualification (IQ), Operating Qualification (OQ), Further details see 208

STANDARD



OPTION





































FACTORY



Model	Weighing capacity [Max] g	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Linearity g	Weighing plate	Option			
							Verification		DAkkS Calibr. Certificate	
							M KERN		DAkkS KERN	
KERN										
PLS 420-3F	420	0,001	-	-	± 0,004	A	-		963-127	
PLS 720-3A	720	0,001	-	-	± 0,002	A	-		963-103	
PLS 1200-3A	1200	0,001	-	-	± 0,003	A	-		963-103	
PLS 4200-2F	4200	0,01	-	-	± 0,04	B	-		963-127	
PLS 6200-2A	6200	0,01	-	-	± 0,03	B	-		963-104	
PLS 8000-2A	8200	0,01	-	-	± 0,04	B	-		963-104	
PLS 20000-1F	20000	0,1	-	-	± 0,4	C	-		963-128	
PLJ										
PLJ 420-3F	420	0,001	-	-	± 0,003	A	-		963-127	
PLJ 720-3A	720	0,001	-	-	± 0,002	A	-		963-103	
PLJ 1200-3A	1200	0,001	-	-	± 0,003	A	-		963-103	
PLJ 2000-3A	2100	0,001	-	-	± 0,004	A	-		963-103	
PLJ 4200-2F	4200	0,01	-	-	± 0,04	B	-		963-127	
PLJ 6200-2A	6200	0,01	-	-	± 0,03	B	-		963-104	
Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.										
PLJ 720-3AM	720	0,001	0,01	0,02	± 0,002	A	965-216		963-103	
PLJ 6200-2AM	6200	0,01	0,1	0,5	± 0,03	B	965-217		963-104	

Pictograms

	Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)		KERN Communication Protocol (KCP): It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems		Suspended weighing: Load support with hook on the underside of the balance
	Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required				Battery operation: Ready for battery operation. The battery type is specified for each device
	Easy Touch: Suitable for the connection, data transmission and control through PC or tablet.		GLP/ISO log: The balance displays serial number, user ID, weight, date and time, regardless of a printer connection		Rechargeable battery pack: Rechargeable set
	Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.		GLP/ISO log: With weight, date and time. Only with KERN printers.		Universal plug-in power supply: with universal input and optional input socket adapters for A) EU, CH, GB; B) EU, CH, GB, USA; C) EU, CH, GB, USA, AUS
	Alibi memory: Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.		Piece counting: Reference quantities selectable. Display can be switched from piece to weight		Plug-in power supply: 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
	Data interface RS-232: To connect the balance to a printer, PC or network		Recipe level A: The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out		Integrated power supply unit: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
	RS-485 data interface: To connect the balance to a printer, PC or other peripherals. Suitable for datatransfer over large distances. Network in bus topology is possible		Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display		Weighing principle: Strain gauges: Electrical resistor on an elastic deforming body
	USB data interface: To connect the balance to a printer, PC or other peripherals		Totalising level A: The weights of similar items can be added together and the total can be printed out		Weighing principle: Tuning fork: A resonating body is electromagnetically excited, causing it to oscillate
	Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals		Percentage determination: Determining the deviation in % from the target value (100 %)		Weighing principle: Electromagnetic force compensation: Coil inside a permanent magnet. For the most accurate weighings
	WiFi data interface: To transfer data from the balance to a printer, PC or other peripherals		Weighing units: Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details		Weighing principle: Single cell technology: Advanced version of the force compensation principle with the highest level of precision
	Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.		Weighing with tolerance range: (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model		Verification possible: The time required for verification is specified in the pictogram
	Analogue interface: to connect a suitable peripheral device for analogue processing of the measurements		Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value		DAKkS calibration possible (DKD): The time required for DAKkS calibration is shown in days in the pictogram
	Interface for second balance: For direct connection of a second balance		Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.		Factory calibration (ISO): The time required for Factory calibration is shown in days in the pictogram
	Network interface: For connecting the scale to an Ethernet network				Package shipment: The time required for internal shipping preparations is shown in days in the pictogram
					Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram

*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.

KERN – Precision is our business

Your KERN specialist dealer:

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg – 2500 kg. In combination with a DAKkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAKkS calibration laboratory today is one of the most modern and best-equipped DAKkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAKkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAKkS calibration of balances with a maximum load of up to 50 t
- DAKkS calibration of weights in the range of 1 mg – 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAKkS calibration certificates in the following languages DE, EN, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

