









## FREESTANDING FRIDGE-FRE COMBI SOLID DOOR 324L WHITE









- Operating Temperature Range of +2° C to +10° C for Fridge and -18° C to -25° C for Freezer \*
  Conforms to MHRA guidelines
- NEW Advanced Controller
  Records temperatures accurate to 0.1° C
- NEW Unique Anti Microbial Handle
  Helps prevent the growth of bacteria and minimise the potential for cross contamination
- 2 Fitted Locks as Standard (one on fridge, one on freezer)

Maintains security and ensures the unit can only be accessed by approved personnel

- Fitted Rollers
  For ease of movement
- Wire Shelves
  Enables optimum air flow inside unit
- \*lastic Baskets and Door Organisers

  Maximises space and offers protection to contents

SKU CODE: PRODUCT CODE: DESCRIPTION:

444441790 LSC324UK Freestanding Fridge-freezer Combi Solid Door 324L White

<sup>\*</sup> These are the set temperatures. Please contact us if you require guaranteed chamber temperatures.









## FULL SPECIFICATION – LSC324UK FREESTANDING LABORATORY FRIDGE-FREEZER COMBI SOLID DOOR 324L WHITE

| 具際概息 |
|------|
|      |
|      |

|                                  | BI SOLID DOOR 324L WHITE                                             |  |
|----------------------------------|----------------------------------------------------------------------|--|
| Description                      | Freestanding                                                         |  |
| SKU Code                         | 444441790                                                            |  |
| EAN Code                         | 5052263017900                                                        |  |
| GDPA Code                        | LSC324UK                                                             |  |
| Gross Capacity (L)               | 324 (Fridge: 190, Freezer: 134)                                      |  |
| Net Capacity (L)                 | 302                                                                  |  |
| Unit External Width (mm)         | 600                                                                  |  |
| Unit External Depth (mm)         | 600                                                                  |  |
| Unit External Height (mm)        | 1870                                                                 |  |
| Product Weight (kg)              | 70                                                                   |  |
| Packed Width (mm)                | 657                                                                  |  |
| Packed Depth (mm)                | 734                                                                  |  |
| Packed Height (mm)               | 1885                                                                 |  |
| Packed Weight (kg)               | 78                                                                   |  |
|                                  | UK                                                                   |  |
| Country of Origin                | -                                                                    |  |
| Internal Dimensions (mm) (WxDxH) | Fridge: 510 x 430 x 805, Freezer: 463 x 445 x 780 (step:250d x 260h) |  |
| External Finish                  | White                                                                |  |
| Internal Finish                  | White                                                                |  |
| Type of Plastic                  | SRL800 (HIPS/ABS Mix)                                                |  |
| Temperature Range                | Fridge: +2° C to +10° C, Freezer: -18° C to -25° C                   |  |
| Colour                           | White/Green                                                          |  |
| Door Type                        | Solid                                                                |  |
| Door Style                       | Hinged, Reversible                                                   |  |
| Door Open Depth (mm)             | 1190                                                                 |  |
| Replacement Door Seal            | No                                                                   |  |
| Open Door Sensor                 | Yes                                                                  |  |
| Lock                             | Yes                                                                  |  |
| Adjustable Feet                  | 2 adjustable feet, 2 rear rollers                                    |  |
| Temperature Display on Panel     | Yes                                                                  |  |
| Temperature Alarm                | Yes                                                                  |  |
| Number of Shelves                | 3 (Fridge)                                                           |  |
| Number of Shelf Positions        | 6                                                                    |  |
| Shelf Size                       | 3: 320 x 505 x 4.5                                                   |  |
| Shelf Material                   | Wire                                                                 |  |
| Moulded Drawers                  | 2 Solid half (Fridge)                                                |  |
| Adjustable Door Bins             | 2 full + 4 half                                                      |  |
| Interior Light                   | No                                                                   |  |
| Fan                              | No                                                                   |  |
| Spark Free                       | Yes                                                                  |  |
| Auto or Manual defrost           | Fridge: Automatic, Freezer: Manual                                   |  |
| Controller type                  | Digital, External                                                    |  |
| Climate Class                    | N ,                                                                  |  |
| Refrigerant Type                 | R600a                                                                |  |
| CFC Free                         | Yes                                                                  |  |
| HFC Free                         | Yes                                                                  |  |
| HCFC Free                        | Yes                                                                  |  |
| UK 3 Pin Plug                    | Yes                                                                  |  |
| Other Plug Types Available       | Yes                                                                  |  |
| Voltage Supply                   | 230                                                                  |  |
| Power Consumption                | 1.25 kWh/24 hours                                                    |  |
| Full Load Current                | 1.9 amps                                                             |  |
| Operating Current                | 0.8 amps                                                             |  |
| Aux Output                       | Yes                                                                  |  |
| Insulation Thickness (mm)        | 60                                                                   |  |
| Insulation Type                  | Cyclopentane                                                         |  |
| modiation rype                   | gaopentane                                                           |  |



## **Wolf Laboratories Limited**

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





