Laboratory Plus Bluetooth Enabled Refrigerator

158L Laboratory Plus Upright Fridge with Solid Door

GDMA codeLSFSR158BT-UKSKU code444411358





Key features

- \checkmark Local monitoring and alarm history via Bluetooth
- ✓ Lec Medical Smartphone App compatible
- ✓ Access Port Factory fitted 16mm porthole
- \checkmark Spark-free interior to reduce risk of ignition



Bluetooth Connected Controller

Local temperature monitoring and alarm history via Bluetooth connectivity.



Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.



Spark-free

We have removed

items such as fans

interior of the fridge

igniting flammable

and lights so the

has no chance of

liquids.

Access port

Factory fitted 16mm porthole enables quick and easy access for any secondary temperature monitoring probes.



Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.

Specification: 158L Laboratory Plus Upright Fridge with Solid Door

	1501
Gross Capacity (litres)	158L 158L
Net Capacity (litres)	
Unit External Width (mm)	595mm
Unit External Depth (mm)	660mm
Unit External Height (mm)	850mm
Product Weight (kg)	33.25kg
Packed Width (mm)	640mm
Packed Depth (mm)	660mm
Packed Height (mm)	910mm
Packed Weight (kg)	37.82Kg
Internal Dimensions (mm) (WxDxH)	500mm x 450mm x 725mm
Temperature Range	+2°C to +10°C
Colour	White/green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / Solid
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Balcony
Number of Door Trays	3
Number of Door Tray Positions	4
Door Open Depth (mm)	
Replacement Door Seal	Yes
•	Yes
Open Door Sensor	Yes, 2 Keys
Lock	
Adjustable Feet (number & position) Porthole	4 All adjustable
	Yes
Porthole Size	16 mm
Porthole Location	Rear Bottom
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves/Drawers	4
Number of Shelf Positions	5
Shelf Size (mm) (WxDxH)	495mm x 325mm x 6mm
Shelf Material	Polythene Coated Wire
Drawer Size (mm) (WxDxH)	n/a
Drawer Material	n/a
Number of Baskets	1
Basket Material	Polythene Coated Wire
Basket Size (mm) (WxDxH)	485mm x 180mm x 171mm
Interior Light	No
Fan	No
Spark Free	Yes
Defrost setting	Auto (Off Cycle)
Controller Type	Digital, External
Bluetooth	Yes
Number of Probes]
Probe Type	Air
Ambient Temperature Range	10°C to 32°C
Refrigerant Type	R600a
UK 3 Pin Plug	Yes
Other Plug Types Available	Yes
Voltage Supply (v)	220-240V
Insulation Thickness (mm)	45mm
Insulation Type Blowing Agent	High Density Polyurethane Foam Cyclopentane
	()vclopentane
Anti Microbial Handle	Yes



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





