





Fitted with a digital lock to solve the issue of lost keys and generic fridge locks and powered by the NEW IntelliCold[®] touch screen controller, this pharmacy refrigerator is packed with extra functions designed to store temperature sensitive pharmaceuticals in optimum conditions including a 1 metre secondary (wandering) temperature probe and automatic fridge function and temperature data recording.



The touch screen, which is completely flat so can be thoroughly cleaned and disinfected, displays, alarms and records minimum and maximum temperatures for both temperature probes. Like a mobile phone touch screen, the screen locks after 30 seconds to ensure that buttons can't be activated accidently.

There is a master key (optional extra) you can purchase so you can access the contents if the code is forgotten or there is an electrical failure and batteries aren't fitted to the fridge. For a small additional cost we can also provide a manufacturers' calibration certificate from our UKAS temperature calibration laboratory No:8898.

We are confident that this pharmacy refrigerator will provide you with many years of fault free service. However, for extra peace of mind your RLDF0119DIGILOCK comes complete with a FREE UK 5 year parts and labour warranty.





While you're registering your warranty, why not purchase a micro SD card for transferring all the data recorded by the controller from the fridge to your computer? The IntelliCold® controller automatically records fridge function and temperature data for both probes at minute intervals plus all alarm states. This data can only be transferred to a computer via a specially encoded micro SD card. This data not only helps you with record keeping and breeze through regulatory inspections it is also useful if you have an issue to establish the exact duration and severity of any event.

RLDF0119DIGILOCK Pharmacy & Vaccine Refrigerator

Part Number	RLDF0119DIGILOCK
Capacity (Litres)	36
Style	Bench Top
Exterior Dimensions (HxWxD)	540 x 450 x 510mm
Interior Dimensions (HxWxD)	392 x 331 x 226mm
Operating Temperature	+5°C
Temperature Range	+2°C to +8°C
Power Consumption Kwh/24hrs	1.28
Interior Construction	Moulded Plastic
Exterior Construction	Powder Coated Steel
Brackets for Wall Mounting	\checkmark
Shelves	2
Net Weight (kg)	30
Door Style	Solid
Door Hinging	Right (can be reversed at time of manufacture)
Self Closing Door	\checkmark
Digital Door Lock	\checkmark
Digital Temperature Display	\checkmark
Internal Light	\checkmark
High/Low Temperature Alarm	\checkmark
Minimum/Maximum Temperature Recording	\checkmark
Automatic Temperature & Fridge Function Data Recording	\checkmark
Door Open Alarm	\checkmark
Mains Failure Alarm	\checkmark
Alarm Battery Back-Up	\checkmark
Second Temperature Probe	\checkmark
Off Cycle Auto Defrost	\checkmark
Fan Assisted Cooling	\checkmark
Remote Alarm Contacts	\checkmark
Access Port	\checkmark
DH Green Book Guidelines Compliant	\checkmark





Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





