















Access Port



Door Lock



Digital Microprocessor Controller

Labcold Cooled Incubators are also available in 88 litre, 150 litre and 600 litre capacity

Most models have the choice of glass or solid door

RLCG01502 Refrigerated Cooled Incubator Glass Door

This 150 litre cooled incubator is ideal for microbiology or any application where precise and consistent temperatures at or below room temperature are required.

With a robust painted steel exterior and powder coated steel interior and fully adjustable shelves, this incubator is versatile and built to last.

This model is also available with a glass door, please see **Labcold** model RLCG0502.

Part Number	RLCG01502
Capacity (Litres)	150
Style	Underbench
Exterior Dimensions (HxWxD)	820 x 600 x 600mm
Interior Dimensions (HxWxD)	690 x 510 x 430mm
Weight	43kg
Energy Consumption	2kWh/24hr
Operating Temperature	+5°C to +40°C
Interior Construction	Powder Coated Steel
Exterior Construction	Enamelled Steel
Door Style	Glass
Door Hinging	Right
Lock	Manual Key
Shelves	3
Shelf dimension (WxD)	495 x 3200mm
Spare shelves available	✓
Internal Light	✓
Temperature display	✓
Microprocessor controlled temperature regulation	✓
Fan assisted temperature control	✓
Access Port	✓
Auto Defrost	X
Eco Friendly Refrigerant	√







Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





