

Vacuum Aspiration System



Hydrophobic filter
0.45µm
Φ6mm

Wide range of adapters fit well with tube, microplate and disk plate for various of tasks, all of which can be fully autoclaved.

SafeVac is designed for laboratory waste recovery and separation of liquid and solid. It can be widely used in cell culture, DNA extraction, microplate waste removal, and any other liquid separation or recovery.


SAFEVAC Vacuum Aspiration Systems

Features

- Vacuum power can be set to different levels to achieve 1ml/s to 15ml/s aspiration speed
- Sensitive level sensor to prevent liquid overflow during operation.
- Fully autoclavable waste collection bottle, tubing and handle
- Lid, tubing and handle are easy for disassembling, cleaning and autoclaving
- Wide range of adapters to fit tube, microplate and disk plate for various tasks
- Interchangeable hand operator -tip adapters make it suitable for various tasks from single channel to 8-channel based on the applications in tube, micro plate, disk plate etc.

Specifications

Vacuum range	0-600 mbar
Aspirating speed	1-15 ml/s
Autoclave component	tube; waste bottle; operation handle;
Dimension [W× D× H]	180 × 240 × 450mm
Weight	3 kg
Input voltage	100-240 VAC, 50/60 Hz
Bottle Volume	4L





WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.