



DLAB hematocrit centrifuge with AC24P hematocrit rotor is used for determination of volume fractions of erythrocytes in blood for diagnostic purposes and doping tests. Also it is used for the photometric determination of bilirubin content in neonate blood samples. Hematocrit centrifuge with A24-2P tube rotor, can be used for extraction of DNA and RNA.

DM1424 Hematocrit Centrifuge

Features:

- Speed range of 200-14000rpm, max. RCF 18620×g
- Precise control of speed and time separately
- Easy operation with intuitive menu and easy-to-read display
- Maintenance-free brushless DC motors
- Pulse operation for quick spins
- Rotor capacity: Hematocrit rotor: Hematocrit rotor:24 capillary max. speed:12000rpm Tube rotor: 1.5/2mLx24 max. speed: 14000rpm

DM1224E Economical Hematocrit Centrifuge

Features:

- Max.speed is 12000rpm, max. RCF 13680×g
- Precise control of speed and time separately
- Rotor capacity: Hematocrit rotor: 24 capillary



DM1424 series



CE  FC



CE  FC

Specifications

	DM1424	DM1224E
Speed range	200-14000rpm, increment: 10rpm	300-12000rpm, increment: 100rpm
Max. RCF	18620×g	13680×g
Speed accuracy	±20	±100
Rotor Capacity	2 type	1 type
Run Time	30sec-99min / Continuous	30sec-99min / Continuous
Motor	Brushless DC motor	Brushless DC motor
Display	LCD	LCD
Safety Devices	Door interlock, Overspeed detector; Over-temperature detector, Automatic internal diagnosis, Automatic rotor identification	Door interlock, Imbalance protection
Acceleration/Braking time	30s ↑ 30s ↓	30s ↑ 30s ↓
Power	Single-phase, 220V-240V, 50Hz/60Hz, 5A; 110V-120V, 50Hz/60Hz, 5A 160W	Single-phase, 220V-240V, 50Hz/60Hz, 5A; 110V-120V, 50Hz/60Hz, 5A 160W
Dimension[WxDxH]	280×364×266mm	280×370×220mm
Weight	10kg	8kg
Certification	CE cTUVus FCC MCA IVD	-
Advanced features	Speed/RCF switch; Short-time run function; sound-alert function	Speed/RCF switch; Short-time run function; sound-alert function

Available rotors



A24- 2P

for DM1424

Cat. No. 19400013

Max. speed : 14000rpm

Max. RCF: 18620×g

Rotor capacity: 2mL/1.5mL×24, 0.2mL×24, 0.5mL×24

Rotor material: High strength plastic

Available rotor adapters: A02P2, A05P2, A10P15 & Mat



AC24

for DM1424 & DM1424E

Cat. No. 19400046

Max. speed : 12000rpm

Max. RCF: 13680×g

Rotor capacity: capillary tubes x24

Rotor material: High strength aluminum

Available adapters



A02P2

2mL to 0.2mL rotor adapter, used with A12-2, A12-2P, AS24-2 and A24-2P rotors, 24pcs/pk

Cat. No. 19500001

A05P2

2mL to 0.5mL rotor adapter, used with A12-2, A12-2P, AS24-2 and A24-2P rotors, 24pcs/pk

Cat. No. 19500002

A10P15

Rotor adapter, used with A12-10P, 12pcs/pk

Cat. No. 19500003



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

