Palm Micro Centrifuges

D1008 series

Palm Micro Centrifuge

Features

- Ideal for microfiltration and quick spin-downs
- Easy-to-use with dual start/stop function
- 7000rpm fixed speed (D1008)
- 5000rpm fixed speed (D1008E)
- Compatible with 2mL x 8 and PCR8 x 2 rotors
- Quiet running, noise level ≤45 dB
- Rotor change without tools
- Accelerates and brakes in seconds
- Four colors available, green, blue, yellow and pink, add color to your routine laboratory life



Quiet operation



Vibration free







Specifications	D1008	D1008E
Max. Speed	7000rpm	5000rpm
Max. RCF	2680×g	1360×g
Rotor Capacity	0.2/0.5/1.5/2.0mL×8; 0.2mL×16 PCR strips or 0.2mL×2 PCR 8 strips	0.2/0.5/1.5/2.0mL×8; 0.2mL×16 PCR strips or 0.2mL×2 PCR 8 strips
Run Time	Continuous operation	Continuous operation
Driving Motor	DC motor	DC motor
Power	AC110-240V/50Hz/60Hz 20W	AC110-240V/50Hz/60Hz 20W
Noise level	≤45dB	≤45dB
Dimension [D×W×H]	160 x 170 x 122mm	160 x 170 x 122mm
Weight	0.5kg	0.5kg
Certification	CE cTÜVus FCC MCA	CE cTÜVus FCC MCA

Palm Micro Centrifuges | Rotors and Adapters

Available rotors



A08-2

Cat. No. 19400015

Max. speed:10000/7000/5000rpm
Max. RCF:5460/2680/1360×g
Rotor capacity:2mL/1.5mL×8,0.2mL×8,0.5mL×8
Rotor material:High strength plastic
Available rotor adapters:SA02P2, SA05P2



A02-PCR8

Cat. No. 19400017

Max. speed:10000/7000/5000rpm Max. RCF:5460/2680/1360×g

Rotor capacity:0.2mL×16 PCR strips,0.2 mL×2 PCR 8 strips

Rotor material: High strength plastic

Available adapters



SA02P2

Cat. No. 19400029

0.2mL rotor adapter Used with A08-2 rotor 8pcs/pk



SA05P2

Cat. No. 19400026

0.5mL rotor adapter Used with A08-2 rotor 8pcs/pk



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





