



D2012 plus High Speed Mini Centrifuge

Features

- Powerful centrifugal force of 15100xg and max speed of 15000rpm ideal for various applications
- Brushless DC motor drive quickly accelerates the rotor to set speed
- Quiet working, Low noise ≤ 56 dB
- D2012 is proven by IEC/EN 61010-1
- D2012 Plus passed the rigorous explosion-proof test and accredited with CE, cTUVus, FCC certificates, and MCA test. MCA test according to IEC/EN61010-2-20



Brushless DC motor



LCD display



CE  FCC



Specifications

	D2012 plus
Max. Speed	15000rpm (500-15000rpm), increment:100rpm
Max. RCF	15100xg, increment:100xg
Speed Accuracy	± 20 rpm
Rotor Capacity	0.2mL/0.5mL/1.5mL/ 2mLx12
Run Time	30sec-99min / Continuous
Driving Motor	Brushless DC motor
Safety Devices	Door interlock, Over-speed detection, Over-temperature detection, Automatic internal diagnosis
Power	Single-phase, AC110V-240V, 50Hz/60Hz, 3A 100W
Noise level	≤ 54 dB
Acceleration /Braking time	11s \uparrow /9s \downarrow
Dimension [DxWxH]	255x245x140mm
Weight	6kg
Certification	EMC, CE, FCC, ICES, cTUVus, CB
Advanced features	Speed/RCF switch, Short-time run function, sound-alert function

D2012 series | Rotors and Adapters

Available rotors



Cat. No. 19400010

A12-2P

for D2012plus only

Max. speed :15000rpm

Max. RCF:15100xg

Rotor capacity:2mL/1.5mLx12,0.2mLx12,0.5mLx12

Rotor material:High strength plastic

Available rotor adapters:A02P2,A05P2

Available adapters



Cat. No. 19500001

A02P2

0.2mL rotor adapter

Used with A12-2, A12-2P, AS24-2 and A24-2P rotors

24 pcs/pk

Cat. No. 19500002

A05P2

0.5mL rotor adapter

Used with A12-2,A12-2P, AS24-2 and A24-2P rotors

24 pcs/pk





Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

