### **Shakers**

DLAB rocking and 3D shakers provide perfect solution in electrophoresis gel dyeing/discoloration, sample washing, molecular hybridization, immunoprecipitation, Western blot and cell culture.

### SK-R330-Pro

### **LCD Digital Rocking Shaker**

#### **Features:**

- Rocking motion angle 9°
- Max. load capacity is 10kg with platform
- Speed range of 10-70rpm
- Double LCDs for independent display time and speed
- Wide range of platforms for use with a variety of vessels





# **SK-R1807-S LED Digital Rocking shaker**

#### **Features:**

- Rocking motion angle 7°
- Max. load capacity is 3kg with platform
- Speed range of 10-80rpm
- Double LEDs for independent display time and speed
- Wide range of platforms for use with a variety of vessels

# **SK-R1807-E Economical Rocking Shaker**

#### **Features:**

- Rocking motion angle 7°
- Max. load capacity is 3kg with platform
- Speed range of 0-80rpm
- Wide range of platforms for use with a variety of vessels











Wide range of accessories







| Specifications |  |
|----------------|--|
| Tilt angle     |  |

| Tilt angle                            |  |  |  |  |  |
|---------------------------------------|--|--|--|--|--|
| Max. load capacity<br>(with platform) |  |  |  |  |  |
| Motor type                            |  |  |  |  |  |
| Motor input power                     |  |  |  |  |  |
| Motor output power                    |  |  |  |  |  |
| Speed range                           |  |  |  |  |  |
| Speed display                         |  |  |  |  |  |
| Timer display                         |  |  |  |  |  |
| Time settings range                   |  |  |  |  |  |
| Voltage                               |  |  |  |  |  |
| Power                                 |  |  |  |  |  |
| Weight                                |  |  |  |  |  |
| Permissible ambient temperature and   |  |  |  |  |  |
| humidity                              |  |  |  |  |  |
| Dimension[W×D×H]                      |  |  |  |  |  |
| Protection class                      |  |  |  |  |  |

| 510 11350 1 13   |
|------------------|
| 9°               |
| 10kg             |
| DC motor         |
| 40W              |
| 24W              |
| 10-70rpm         |
| LCD              |
| LCD              |
| 1min-19h59min    |
| 100-240V,50/60Hz |
| 50W              |
| 9kg              |
| 5-40°C,80%RH     |
| 360×410×200mm    |

### SK-R1807-S

| 7°               |
|------------------|
| 3kg              |
| DC motor         |
| 16W              |
| 10W              |
| 10-80rpm         |
| LED              |
| LED              |
| 1min-19h59min    |
| 100-240V,50/60Hz |
| 20W              |
| 3.2kg            |
| 5-40°C,80%RH     |

270×330×130mm

## SK-R1807-E 7°

3kg

| DC motor         |  |  |  |  |  |
|------------------|--|--|--|--|--|
| 16W              |  |  |  |  |  |
| 10W              |  |  |  |  |  |
| 0-80rpm          |  |  |  |  |  |
| -                |  |  |  |  |  |
| -                |  |  |  |  |  |
| -                |  |  |  |  |  |
| 100-240V,50/60Hz |  |  |  |  |  |
| 20W              |  |  |  |  |  |
| 3.2kg            |  |  |  |  |  |
| 5-40°C,80%RH     |  |  |  |  |  |
| 270×330×130mm    |  |  |  |  |  |





# **SK-D3309-Pro LCD Digital 3D Shaker**

### **Features:**

- Three-dimensional rocking motion with an angle of 9°
- Max. load capacity is 5kg with platform
- Speed range of 10-70rpm
- Double LCDs for independent display time and speed
- Various of platform accessories



# **SK-D1807-S**LED Digital 3D shaker

#### **Features:**

- Three-dimensional rocking motion with the angle of 7°
- Max. load capacity is 3kg with platform
- Speed range of 10-80rpm
- Double LEDs for independent display time and speed
- Various of platform accessories





# SK-D1807-E Economical 3D Shaker

#### **Features:**

- Three-dimensional rocking motion with the angle of 7°
- Max. load capacity is 3kg with platform
- Speed range of 0-80rpm
- Wide range of platforms for use with a variety of vessels

## **Shakers**





Timer



Wide range of accessories







| C-  |    | -:- | :   | 45.4 |    |
|-----|----|-----|-----|------|----|
| > p | )e | CIT | ıca | TIC  | ns |

| Tilt angle                            |
|---------------------------------------|
| Max. load capacity<br>(with platform) |
| Motor type                            |
| Motor input power                     |
| Motor output power                    |
| Speed range                           |
| Speed display                         |
| Timer display                         |
| Time settings range                   |
| Voltage                               |
| Power                                 |
| Weight                                |
| Permissible ambient temperature and   |
| humidity                              |
| Dimension[W×D×H]                      |
| Protection class                      |
| Data connector                        |

| SK-D3309-Pro     | SK-D1807-S       | SK-D1807-E       |
|------------------|------------------|------------------|
| 9°               | 7°               | 7°               |
| 5kg              | 3kg              | 3kg              |
| DC motor         | DC motor         | DC motor         |
| 40W              | 16W              | 16W              |
| 24W              | 10W              | 10W              |
| 10-70rpm         | 10-80rpm         | 0-80rpm          |
| LCD              | LED              | scale            |
| LCD              | LED              | -                |
| 1min-19h59min    | 1min-19h59min    | -                |
| 100-240V,50/60Hz | 100-240V,50/60Hz | 100-240V,50/60Hz |
| 50W              | 20W              | 20W              |
| 9kg              | 2.7kg            | 2.7kg            |
| 5-40°C, 80%RH    | 5-40°C, 80%RH    | 5-40°C, 80%RH    |
| 360×430×106mm    | 270×330×130mm    | 270×330×130mm    |
| IP21             | IP21             | IP21             |
|                  |                  |                  |

# **Shakers** | Accessories

|         |          |  | SK-O330-Pro                                | SK-O180-Pro/S/E                                 |
|---------|----------|--|--|---|
|         | Cat. No. | Description  | SK-L330-Pro<br>SK-R330-Pro<br>SK-D3309-Pro | SK-L180-Pro/S/E<br>SK-R1807-S/E<br>SK-D1807-S/E |
| SK330.5 | 18900155 | Dish platform with non-slip mat and<br>fixed string (8 pcs)<br>Dimension[WxD]: 30x28.5cm | •  |   |
| SK180.4 | 18900185 | Dish attachment with non-slip mat<br>Dimension[WxD]: 24x21.5cm                           |  | •   |
| SK180.5 | 18900200 | Large size dish attachment with<br>non-slip mat<br>Dimension[WxD]: 30x23cm               |  | •   |
| SK180.6 | 18900326 | Dish attachment with non-slip mat<br>Dimension[WxD]: 28x28cm                             |  | •   |
| SK330.1 | 18900027 | Universal attachment with 4 bars<br>Dimension[WxD]: 30x30cm                              | •  |   |
| SK330.3 | 18900040 | Lengthways roller attachment<br>Dimension[WxD]: 30x30cm                                  | •  |   |
| SK180.1 | 18900025 | Universal attachment with 3 bars<br>Dimension[WxD]: 24x24cm                              |  | •   |
| SK180.3 | 18900038 | Lengthways roller attachment<br>Dimension[WxD]: 24x24cm                                  |  | •   |
| •       | 18900036 | Bar for SK330.1 universal<br>attachment  | •  |   |
|         | 18900037 | Bar for SK180.1 universal<br>attachment  |  | •   |
|         | 18900280 | Connect sticks<br>for double dishes shaker   | •  | •   |

# **Shakers** | Accessories

| T R |          |  |   |  |
|-----|----------|--|---|--|
|     | Cat. No. | Description  | SK-O330-Pro<br>SK-L330-Pro<br>SK-R330-Pro<br>SK-D3309-Pro | SK-O180-Pro/S/E<br>SK-L180-Pro/S/E<br>SK-R1807-S/E<br>SK-D1807-S/E   |
|     | 18900028 | Fixing clip attachment   | •   |  |
|     | 18900026 | Fixing clip attachment   |   | •  |
| B   | 18900029 | Fixing clip for flask volume<br>25mL, used with<br>SK330.2[28pcs]<br>SK180.2 [9pcs]      | •   | •  |
| B   | 18900030 | Fixing clip for flask volume<br>50mL, used with<br>SK330.2[16pcs]<br>SK180.2 [9pcs]      | •   | •  |
| B   | 18900031 | Fixing clip for flask volume<br>100mL, used with<br>SK330.2[16pcs]<br>SK180.2 [9pcs]     | •   | •  |
| B   | 18900032 | Fixing clip for flask volume<br>200/250 ml, used with<br>SK330.2[9pcs]<br>SK180.2 [4pcs] | •   | •  |
| B   | 18900033 | Fixing clip for flask volume<br>500mL, used with<br>SK330.2[9pcs]<br>SK180.2 [2pcs]      | •   | •  |
|     |          | 18900028  18900026  18900029  18900030  18900031   | 18900028   Fixing clip attachment                         | Table   Tabl |



# **Wolf Laboratories Limited**

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





