



Upright Laboratory Control Plus Fridge-Freezer Combi 324L ATEX

GDPA code: LSFC324UK-ATEX Lab ATEX UP F/F

SKU code: 444410681

- ✓ Operating Temperature Range of +2°C to +10°C for Fridge and -18°C to -25°C for Freezer
- ✓ Spark Free
- ✓ Advanced Controller
- ✓ Unique Anti Microbial Handle
- ✓ 2 Fitted Locks as Standard



The Experts in
Medical Refrigeration

Specification: Upright Laboratory Control Plus Fridge-Freezer Combi 324L ATEX

Gross Capacity (litres)	324 (Fridge: 190, Freezer: 134)
Net Capacity (litres)	302
Unit External Width (mm)	600
Unit External Depth (mm)	600
Unit External Height (mm)	1870
Product Weight (kg)	70
Packed Width (mm)	657mm
Packed Depth (mm)	734mm
Packed Height (mm)	1885mm
Packed Weight (kg)	78kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	Fridge: 510 x 430 x 805, Freezer: 463 x 445 x 780 (step: 250d x 260h)
Temperature Range	Fridge: +2°C to +10°C, Freezer: -18°C to -25°C
Colour	White/Green
External Finish	White
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / Solid
Door Type	Solid
Door Style	Hinged, Reversible
Door Open Depth (mm)	1190mm
Replacement Door Seal	No
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	2 adjustable feet, 2 rear rollers
Porthole	No
Porthole Size	N/A
Porthole Location	N/A
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves	3 (Fridge)
Number of Shelf Positions	6
Shelf Size (mm) (WxDxH)	320 x 505 x 4.5
Shelf Material	Wire
Number of Baskets	0
Basket Material	2 Solid half (Fridge)
Basket Size (mm) (WxDxH)	2 full + 4 half
Interior Light	N/A
Light Type	No
Light Activation	N/A
Fan	N/A
Spark Free	No
Auto or Manual Defrost	Yes
Controller Type	Fridge: Automatic, Freezer: Manual
Number of Probes	Digital, External
Probe Type	1
Climate Class	Air
Refrigerant Type	N
CFC Free	R600a
HFC Free	Yes

Specification: Upright Laboratory Control Plus Fridge-Freezer Combi 324L ATEX

HCFC Free	Yes
Ammonia Free	Yes
UK 3 Pin Plug	Yes
Other Plug Types Available	Yes
Noise Level (dB)	Yes
Energy Consumption (kwh)	-
Voltage Supply	1.25 kWh/24 hours
Aux Output	230
Insulation Thickness (mm)	Yes
Insulation Type	60mm
Blowing Agent	Cyclopentane
Anti Microbial Handle	Yes
Optional Drawer System Available	No
Wall Brackets	No
Digital Lock	No



Wolflabs

Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

