## **LKUv 1613**

## MediLine

Gross/net capacity	152/143 litre
Ext. dimensions in mm (w/d/h)	597/615/820
Int. dimensions in mm (w/d/h)	440/435/670
Energy consumption in 365 days	369 kWh
Climate rating	SN-ST <sup>1</sup>
Refrigerant	R 600a
Airborne acoustical noise emissions	47 dB(A)
Connection Rating	1.0 A
Voltage	220-240 V~
Cooling system	forced- ir
Defrosting	utom tic
Temperature range	+2°C to +8°C
Gradient *	5.1°C
Max. fluctuation **	4.9°C
Housing material/colour	steel/white
Door/lid material	Insul ted gl zed door
Liner Material	moulded polystyrol white
Type of Control	electronic controller
Temperature display	extern I digit I
Interior light	LED
Fault: warning signal	visu I nd udible
Interface	RS 485
volt-free alarm contact	yes
Evaporator Cover	yes
Adjustable Shelving	3
Shelf material	grid shelves pl stic-co ted
Shelf loading	45 kg
Handle	Ergonomic door h ndlefitte
Lock	d
Self-closing door	yes
Door hinges	right, reversible
Insulation	40 mm
Gross/net weight	46 / 43 kg
EAN-Nr.	9005382193235



<sup>\*</sup> Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

\*\*\* Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.



## **Wolf Laboratories Limited**

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





