

Chest freezer XLT C75



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable
- Efficient cyclopentane insulation
- Eco-friendly, HCFC-free Nature R refrigerant
- ISO 9001, 14001 & 18001 OHSAS Certified

Specifications

Technical

Gross volume	74 litres
Net Volume	71 litres
Temp. range	-45°C to -65°C
Temp. probes	1/PT 1000
Compressor	Secop
Baskets (incl./optional)	1/1
Refrigerant	Nature R
Noise level	55 dB
Power consumption 24/h	4,0 kWh
Power consumption	1.460 kWh / year
Voltage	230V
Frequency	50 Hz

Features

Audible and visual alarm	YES
Castors	NO
Integrated lock	YES
Inner lids	NO
Defrost	Manual
Battery Backup	NO
USB	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø12 mm
Prepared for external logging equipment	YES

Material

Inner	Precoated white steel
Outer	Galvanized pre-coated steel

Outer dimensions

Height	900 mm
Width	555 mm
Depth (incl. condenser)	580 mm
Depth (incl. condenser & handle)	630 mm
Net weight	48 kg

Inner dimensions

Height	465 mm
Width	390 mm
Depth	390 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %

XLT C75



Product no.

N112001

Storage capacity

Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
50 mm	8	5	40	N311210
75 mm	5	5	25	N311310
100 mm	4	5	20	N311410



Wolf Laboratories Limited

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk



Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

