### Chest freezer ULT C200



- Low cost of ownership
- Limited maintenance and On-site service
- Easily installable & movable

- Efficient cyclopentane insulation
- Eco-friendly, HCFC-free Nature R refrigerant
- ISO 9001, 14001 & 18001 OHSAS Certified

# Specifications Technical

Gross volume 198 litres Net volume 189 litres -60°C to -86°C Temp. range Temp. probes 1/PT 1000 Compressor Embraco Refrigerant Nature R Noise level 55 dB 6,0 kWh Power consumption 24/h Power consumption 2.190 kWh/year 220V-240V Voltage 50 Hz Frequency

#### Features

Audible & visual alarm YES Castors 4 Integrated lock YES Inner lids Manual Defrost Battery Backup 50h NO USB NO Data connection Digital controller with display XR30CX Data logging NO YES High/Low temperature alarm Porthole for external probe & CO2 backup Ø12 mm Prepared for external logging equipment YES Contact for remote alarm YES

#### Material

Inner Precoated white steel
Outer Galvanized pre-coated steel

#### Dimensions

Height 850 mm
Height w. castors 890 mm
Width 920 mm
Depth 695 mm
Net weight 64 kg

#### Internal dimensions

 Height
 635/385 mm

 Width
 550/210 mm

 Depth
 440 mm

 Insulation
 80 mm

 Insulation type
 PUR

 Internal humidity
 <5 %</td>



Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
50 mm	6 11	3 9	18 99 <b>= 117</b>	N311200 N311220
75 mm	4	3	12	N311300

Storage capacity

75 mm	1 4	3	12	N311300
	8	9	72	N311320
			= 84	
100 mr	m 3	3	9	N311400
	5	9	45	N311420
			= 54	



## **Wolf Laboratories Limited**

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





